

ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY
NATIONAL FLOOD INSURANCE PROGRAM

O.M.B. NO. 3067-0077
Expires May 31, 1996

NOTE: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION

OWNER'S NAME PATRICK Goodles	FOR INSURANCE COMPANY USE
PROPERTY ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER 9 TAMMY'S Circle	POLICY NUMBER
DESCRIPTION (Lot and Block Numbers, etc.) Lot 272, Phase IX, GARDEN ACRES Pooler	COMPANY NAIC NUMBER

STATE: **GA.** ZIP CODE: **31322**

SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

Obtain the following from the proper FIRM (See Instructions):

1. COMMUNITY NUMBER 130030	2. PANEL NUMBER 20	3. SUFFIX C	4. DATE OF FIRM INDEX MAY 19, 1987	5. FIRM ZONE AE	6. BASE FLOOD ELEVATION (In AO Zones, use depth) 14.0
--------------------------------------	------------------------------	-----------------------	--	---------------------------	---

Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 Other (describe on back) Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate community's BFE: feet NGVD (or other FIRM datum—see Section B, Item 7).

SECTION C BUILDING ELEVATION INFORMATION

Following the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describe the subject building's reference level. If diagrams A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of **116.16** feet NGVD (or other FIRM datum—see Section B, Item 7).

For FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of feet NGVD (or other FIRM datum—see Section B, Item 7).

For FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is feet above or below (check one) the highest grade adjacent to the building.

For FIRM Zone AO. The floor used as the reference level from the selected diagram is feet above or below (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? Yes No Unknown

Indicate the elevation datum system used in determining the above reference level elevations: NGVD '29 Other (describe on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion under Comments on Page 2.)

The elevation reference mark used appears on FIRM: Yes No (See Instructions on Page 4)

The reference level elevation is based on: actual construction construction drawings

NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate is required once construction is complete.)

The elevation of the lowest grade immediately adjacent to the building is: **115.17** feet NGVD (or other FIRM datum—see Section B, Item 7).

SECTION D COMMUNITY INFORMATION

The community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: feet NGVD (or other FIRM datum—see Section B, Item 7), effective as of the start of construction or substantial improvement.

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1-A30, AE, AH, A (with BFE), V1-V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.


Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME Terry M. Coleman	LICENSE NUMBER (or Affix Seal) GA R.L.S. No. 2486
TITLE Land Surveyor	COMPANY NAME EMC Engineering Services, Inc.
ADDRESS 23 East Charlton Street	CITY STATE ZIP Savannah GA 31401
SIGNATURE 	DATE PHONE 9/9/98 (912) 232-6533

Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner.

COMMENTS: _____



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.
 Elevations for all A Zones should be measured at the top of the reference level floor.
 Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.