U.S. DEPARTMENT OF HOMELAND SECURITY Federal Emergency Management Agency National Flood Insurance Program

OMB Control No. 1660-0008 Expiration Date: 06/30/2026

ELEVATION CERTIFICATE IMPORTANT: MUST FOLLOW THE INSTRUCTIONS ON PAGES 9-19

Copy all pages of this Elevation Certificate and all attachments for (1) community official, (2) insurance agent/company, and (3) building owner,

SECTION A - PROPERTY INFORMATION	FOR INSURANCE COMPANY USE
A1. Building Owner's Name: Landmark 24 Homes	Policy Number:
A2. Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No.: 161 Champlain Drive	Company NAIC Number:
City: Pooler State: Georgia	ZIP Code: 31322
A3. Property Description (e.g., Lot and Block Numbers or Legal Description) and/or Tax Parcel Nur Lot 1021, Forest Lakes, Phase 10, 8th G.M. District, City of Pooler, Chatham Count	
A4. Building Use (e.g., Residential, Non-Residential, Addition, Accessory, etc.): Residential	
A5. Latitude/Longitude: Lat. 32.145743 Long81.277133 Horizontal Datum:	IAD 1927 🗷 NAD 1983 🗌 WGS 84
A6. Attach at least two and when possible four clear photographs (one for each side) of the building	
A7. Building Diagram Number: 1B	
A8. For a building with a crawlspace or enclosure(s):	
a) Square footage of crawlspace or enclosure(s): $\frac{N/A}{}$ sq. ft.	
b) Is there at least one permanent flood opening on two different sides of each enclosed area?	Yes No No N/A
c) Enter number of permanent flood openings in the crawlspace or enclosure(s) within 1.0 foot Non-engineered flood openings: N/A Engineered flood openings: N/A	above adjacent grade:
d) Total net open area of non-engineered flood openings in A8.c: $\frac{N/A}{}$ sq. in.	
e) Total rated area of engineered flood openings in A8.c (attach documentation – see Instruction	ons): N/A sq. ft.
f) Sum of A8.d and A8.e rated area (if applicable – see Instructions): N/A sq. ft.	
A9. For a building with an attached garage:	
a) Square footage of attached garage: 405 sq. ft.	
b) Is there at least one permanent flood opening on two different sides of the attached garage?	Yes No N/A
c) Enter number of permanent flood openings in the attached garage within 1.0 foot above adjacent Non-engineered flood openings: 1 Engineered flood openings: 3	acent grade:
d) Total net open area of non-engineered flood openings in A9.c: 13 sq. in.	
e) Total rated area of engineered flood openings in A9.c (attach documentation – see Instruction	ons): 660 sq. ft.
f) Sum of A9.d and A9.e rated area (if applicable – see Instructions): 673 sq. ft.	
SECTION B - FLOOD INSURANCE RATE MAP (FIRM) INFOR	RMATION
B1.a. NFIP Community Name: City of Pooler B1.b. NFIP Community Ider	ntification Number: 130261
B2. County Name: Chatham County B3. State: GA B4. Map/Panel No.:	13051C0019 B5. Suffix: H
B6. FIRM Index Date: 08-16-2018 B7. FIRM Panel Effective/Revised Date: 07-07-2	2014
B8. Flood Zone(s): AE B9. Base Flood Elevation(s) (BFE) (Zone AO, use E	Base Flood Depth): 20.0'
B10. Indicate the source of the BFE data or Base Flood Depth entered in Item B9: FIS X FIRM Community Determined Other:	
B11. Indicate elevation datum used for BFE in Item B9: 🔲 NGVD 1929 🔀 NAVD 1988 🔲 Other/	Source:
B12. Is the building located in a Coastal Barrier Resources System (CBRS) area or Otherwise Prote Designation Date: CBRS OPA	ected Area (OPA)?
B13. Is the building located seaward of the Limit of Moderate Wave Action (LiMWA)? 🔲 Yes 🔀	No

Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box	FOR INSURANCE COMPANY USE		
161 Champlain Drive City: Pooler State:Georgia ZIP Code: 31322	Policy Number:		
Gity. State. State. State. Str. Code.		Company NAIC Number:	
SECTION C - BUILDING ELEVATION INFORMATION	(SURVEY F	REQUIRED)	
C1. Building elevations are based on: Construction Drawings* Building Under *A new Elevation Certificate will be required when construction of the building is con		on* 🔀 Finished Construction	
C2. Elevations – Zones A1–A30, AE, AH, AO, A (with BFE), VE, V1–V30, V (with BFE), A99. Complete Items C2.a-h below according to the Building Diagram specified in I Benchmark Utilized: Local Vertical Datum: NA	tem A7. In P		
Indicate elevation datum used for the elevations in items a) through h) below. ☐ NGVD 1929 ☒ NAVD 1988 ☐ Other:			
Datum used for building elevations must be the same as that used for the BFE. Convers If Yes, describe the source of the conversion factor in the Section D Comments area.	ion factor use	ed? Yes No Check the measurement used:	
a) Top of bottom floor (including basement, crawlspace, or enclosure floor):	21.4	x feet meters	
b) Top of the next higher floor (see Instructions):	31.9	x feet meters	
c) Bottom of the lowest horizontal structural member (see Instructions):	N/A	feet meters	
d) Attached garage (top of slab):	19.8	🗶 feet 🗌 meters	
 e) Lowest elevation of Machinery and Equipment (M&E) servicing the building (describe type of M&E and location in Section D Comments area): 	21.3	▼ feet	
f) Lowest Adjacent Grade (LAG) next to building: Natural 🔀 Finished	18.8	x feet meters	
g) Highest Adjacent Grade (HAG) next to building: Natural 🔀 Finished	19.6	🔀 feet 🗌 meters	
 Finished LAG at lowest elevation of attached deck or stairs, including structural support: 	N/A	feet meters	
SECTION D - SURVEYOR, ENGINEER, OR ARCHITE	CT CERTIF	FICATION	
This certification is to be signed and sealed by a land surveyor, engineer, or architect autinformation. I certify that the information on this Certificate represents my best efforts to it false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section	nterpret the d		
Were latitude and longitude in Section A provided by a licensed land surveyor?	. □ No		
Check here if attachments and describe in the Comments area.			
Certifier's Name: Don E. Taylor License Number: 3417			
Title: Professional Land Surveyor		EORG	
Company Name: Coleman Company, Inc.		- GEOSTER	
Address: 1480 Chatham Parkway, Suite 100		* NO. 003417	
City: Savannah State: GA ZIP Code: 3	1405	Thosumas a	
Signature: Date: 07-	18-2024	WARDT	
Telephone: 9127200-3041 / Ext.: Email: DTAYLOR@CCI-SAV.COM		Place Seal Here	
Copy all pages of this Elevation Certricate and all attachments for (1) community official, (2)	insurance ag	ent/company, and (8) building owner.	
Comments (including source of conversion factor in C2; type of equipment and location pt A3: (Plat Book 53, Page 745). A9: Garage vented by (1) one non-engineered vent and (3) three engineered vents. Flood Flaps, LL B9: A 1'(one foot) free board is required by the City of Pooler Damage Prevention Ordinance on all the C2: Benchmark utilized was established using "EGPS" GPS base station network. Elevations shown C2a: Elevation is top of finished floor for living space. C2e: Lowest elevation of machinery servicing the building is the top of the HVAC compressor platform.	.C. Model# FFI new constructi n are reference	NF05. See attached certification.	

Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No.:	FOR INSURANCE COMPANY USE
161 Champlain Drive City: Pooler State: Georgie ZIP Code: 31322	Policy Number: Company NAIC Number:
SECTION E - BUILDING MEASUREMENT INFORMATION (SURVEY I FOR ZONE AO, ZONE AR/AO, AND ZONE A (WITHOUT I	
For Zones AO, AR/AO, and A (without BFE), complete Items E1–E5. For Items E1–E4, use natural gintended to support a Letter of Map Change request, complete Sections A, B, and C. Check the meaniter meters.	
Building measurements are based on: Construction Drawings* Building Under Construction *A new Elevation Certificate will be required when construction of the building is complete.	n* Finished Construction
E1. Provide measurements (C.2.a in applicable Building Diagram) for the following and check the a measurement is above or below the natural HAG and the LAG.	opropriate boxes to show whether the
a) Top of bottom floor (including basement, crawlspace, or enclosure) is:	above or below the HAG.
b) Top of bottom floor (including basement, crawlspace, or enclosure) is:	above or below the LAG.
E2. For Building Diagrams 6–9 with permanent flood openings provided in Section A Items 8 and/or next higher floor (C2.b in applicable Building Diagram) of the building is:	9 (see pages 1–2 of Instructions), the above or below the HAG.
E3. Attached garage (top of slab) is:	above or below the HAG.
E4. Top of platform of machinery and/or equipment servicing the building is:	above or below the HAG.
E5. Zone AO only: If no flood depth number is available, is the top of the bottom floor elevated in ac floodplain management ordinance? Yes No Unknown The local official mu	cordance with the community's st certify this information in Section G.
SECTION F - PROPERTY OWNER (OR OWNER'S AUTHORIZED REPRESEN'	TATIVE) CERTIFICATION
The property owner or owner's authorized representative who completes Sections A, B, and E for Zo sign here. The statements in Sections A, B, and E are correct to the best of my knowledge	one A (without BFE) or Zone AO must
Check here if attachments and describe in the Comments area.	
Property Owner or Owner's Authorized Representative Name:	•
Address:	
City: State:	ZIP Code:
Signature: Date:	
Telephone: Ext.: Email:	
Comments:	

Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No.:	FOR INSURANCE COMPANY USE
161 Champlain Drive	Policy Number:
City: Pooler State: Georg ZIP Code: 31322	Company NAIC Number:
SECTION G - COMMUNITY INFORMATION (RECOMMENDED FOR COMMUNI	TY OFFICIAL COMPLETION)
The local official who is authorized by law or ordinance to administer the community's floodplain management of this Elevation Certificate. Complete the applicable item(s) and sign be	
G1. The information in Section C was taken from other documentation that has been signed engineer, or architect who is authorized by state law to certify elevation information. (In elevation data in the Comments area below.)	
G2.a. A local official completed Section E for a building located in Zone A (without a BFE), Zo E5 is completed for a building located in Zone AO.	one AO, or Zone AR/AO, or when item
G2.b. A local official completed Section H for insurance purposes.	
G3.	ne information in Sections A, B, E and H。
G4.	ement purposes.
G5. Permit Number: G6. Date Permit Issued:	
G7. Date Certificate of Compliance/Occupancy Issued:	
G8. This permit has been issued for: 🗵 New Construction 🗌 Substantial Improvement	
G9.a. Elevation of as-built lowest floor (including basement) of the building:	meters Datum:
G9.b. Elevation of bottom of as-built lowest horizontal structural member:	meters Datum:
G10.a. BFE (or depth in Zone AO) of flooding at the building site:	meters Datum:
G10.b. Community's minimum elevation (or depth in Zone AO) requirement for the lowest floor or lowest horizontal structural member:	meters Datum:
G11. Variance issued? Yes No If yes, attach documentation and describe in the Co	mments area.
The local official who provides information in Section G must sign here. I have completed the information to the best of my knowledge. If applicable, I have also provided specific corrections in the C	
Local Official's Name: Nicole Johnson, ACP, CFM Title: Director NFIP Community Name: City of Posler	of Planning & Development
Telephone: 912-748-7761 Ext.: Email: njohnson @ poole	v-99.90V
Address: 100 Sw Huy 80	0 0
City: Pooler State: 671	4 ZIP Code: 3(3)2
Signature: Mich Orhusum Date: 7/25	2/24
Comments (including type of equipment and location, per C2.e; description of any attachments; and Sections A, B, D, E, or H):	d corrections to specific information in

Building Street Address (includ	ing Apt., Unit, Suite.	. and/or Bldg. No.) o	r P.O. Route and Box No.;	FOR INSURANCE COMPANY USE
161 Champlain Drive		Coordin	21222	Policy Number:
City: Pooler		State: Georg	ZIP Code: 31322	Company NAIC Number:
SECTIO			R HEIGHT INFORMATION R INSURANCE PURPOSE	
to determine the building's firs	t floor height for ins It tenth of a meter i	surance purposes. <mark>:</mark> n Puerto Rico). <i>Rel</i>	Sections A, B, and I must also ference the Foundation Type	be complete Section H for all flood zones be completed. Enter heights to the Diagrams (at the end of Section H complete this section.
H1. Provide the height of the	top of the floor (as	indicated in Founda	ation Type Diagrams) above th	ne Lowest Adjacent Grade (LAG):
 a) For Building Diagram floor (include above-grade subgrade crawlspaces or 	e floors only for buil	ldings with	[] feet	meters above the LAG
 b) For Building Diagram higher floor (i.e., the floor enclosure floor) is: 			feet	meters above the LAG
			in Item H2 instructions) eleva ection H instructions) for the ap	ted to or above the floor indicated by the opropriate Building Diagram?
SECTION I - PRO	PERTY OWNER	(OR OWNER'S	AUTHORIZED REPRESE	NTATIVE) CERTIFICATION
	best of my knowled			st sign here. <i>The statements in Sections</i> cial completed Section H, they should
Check here if attachments	are provided (inclu	ding required photo	os) and describe each attachm	ent in the Comments area.
Property Owner or Owner's Au				
Address				
City:			State:	ZIP Code:
Signature:			Date:	
Telephone	Ext.:	Email:		
Comments:				

IMPORTANT: MUST FOLLOW THE INSTRUCTIONS ON PAGES 9-19

BUILDING PHOTOGRAPHS

See Instructions for Item A6.

Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No.: 161 Champlain Drive		FOR INSURANCE COMPANY USE	
	G	21200	Policy Number:
City: Pooler	State: Georgia ZIP Code:	31322	Company NAIC Number:

Instructions: Insert below at least two and when possible four photographs showing each side of the building (for example, may only be able to take front and back pictures of townhouses/rowhouses). Identify all photographs with the date taken and "Front View," "Rear View," "Right Side View," or "Left Side View." Photographs must show the foundation. When flood openings are present, include at least one close-up photograph of representative flood openings or vents, as indicated in Sections A8 and A9.



Photo One

Photo One Caption: Front View

07-18-2024

Clear Photo One



Photo Two

Photo Two Caption: Rear View

07-18-2024

Clear Photo Two

IMPORTANT: MUST FOLLOW THE INSTRUCTIONS ON PAGES 9-19

BUILDING PHOTOGRAPHS

Continuation Page

FOR INSURANCE COMPANY USE Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No. 161 Champlain Drive Policy Number: City: Pooler State: Georgia ZIP Code: 31322

Insert the third and fourth photographs below. Identify all photographs with the date taken and "Front View," "Rear View," "Right Side View," or "Left Side View." When flood openings are present, include at least one close-up photograph of representative flood openings or vents, as indicated in Sections A8 and A9.



Photo Three

Photo Three Caption: Left View

07-18-2024



Company NAIC Number:



Photo Four

Photo Four Caption: Right View

07-18-2024

Clear Photo Four

ADDITIONAL **BUILDING PHOTOGRAPHS**

ELEVATION CERTIFICATE

Continuation Page

OMB No. 1660-0008 Expiration Date: November 30, 2018

IPORTANT: In these spaces, copy the corresponding information from Section A.			FOR INSURANCE COMPANY USE	
Building Street Address (including 161 Champlain Drive	g Apt., Unit, Suite, and/or Bldg. No.) o	r P.O. Route and Box No.	Policy Number:	
City	State	ZIP Code	Company NAIC Number	
Pooler	Georgia	31322		

If submitting more photographs than will fit on the preceding page, affix the additional photographs below. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." When applicable, photographs must show the foundation with representative examples of the flood openings or vents, as indicated in Section A8.



Photo One Caption

VENTS 07-18-2024



Photo Two Caption

VENT 07-18-2024



ICC-ES Evaluation Report

ESR-3560

Reissued September 2023

This report also contains:

- CBC Supplement

- FBC Supplement

Subject to renewal September 2024

ICC-ES Evaluation Reports are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the report or a recommendation for its use. There is no warranty by ICC Evaluation Service, LLC, express or implied, as to any finding or other matter in this report, or as to any product covered by the report.

Copyright @ 2023 ICC Evaluation Service, LLC. All rights reserved.

DIVISION: 08 00 00 - OPENINGS

0. _....

Section: 08 95 43— Vents/Foundation Flood

Vents

REPORT HOLDER: FLOOD FLAPS®, LLC

EVALUATION SUBJECT:

FLOOD FLAPS® AUTOMATIC FLOOD VENTS: MODELS FFWF12; FFNF12; FFWF08; FFNF08; FFWF05; FFNF05



1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2021, 2018, 2015, 2012 and 2009 International Building Code® (IBC)
- 2021, 2018, 2015, 2012 and 2009 International Residential Code® (IRC)

Properties evaluated:

- Physical operation
- Water flow
- Weathering

2.0 USES

Flood Flaps® automatic flood vents are used to provide for the equalization of hydrostatic flood forces on exterior walls. Certain models also allow natural ventilation.

3.0 DESCRIPTION

3.1 General:

Flood Flaps® automatic flood vents are engineered mechanically operated flood vents (FVs) that automatically allow flood waters to enter and exit enclosed areas. The FVs are constructed of ABS plastic which serves as the FV's housing, and a front grill that contains an anodized metal screen imbedded in polypropylene plastic. On contact with rising flood water, the grill will disengage from its secured position, allowing flood water and debris to flow through in either direction. The FVs are available in two series as described in Section 3.3.

The sealed series models contain two rubber flaps that close the FV to the passage of air when using with conditioned areas or sealed crawl spaces. In the same manner as the grill, the two rubber flaps are pushed open by water pressure, allowing water and debris to flow through the FV in either direction. See <u>Figure 1</u> for an illustration of the Flood Flaps® automatic FV.

3.2 Engineered Opening:

The Flood Flaps® automatic FVs comply with the design principle noted in Sections 2.7.2.2 and 2.7.3 of ASCE/SEI 24-14 (2021, 2018 and 2015 IBC and IRC) [Section 2.6.2.2 of ASCE/SEI 24-05 (2012 and 2009 IBC and IRC)] for a rate of rise and fall of 5 feet per hour (0.423 mm/s). In order to comply with the engineered



opening requirement of ASCE/SEI 24, Flood Flaps® automatic FVs must be installed in accordance with Section 4.0.

3.3 Flood Vent Series Models:

Flood Flaps® automatic FVs are available in two series with multiple models and sizes as described in Table 1. The sealed series models, designated FFWF, include two rubber flaps for the prevention of air flow. The multi-purpose series, designated FFNF, omits the rubber flaps.

3.4 Natural Ventilation:

Flood Flaps® automatic FV models FFNF12, FFNF08, FFNF05, and FFNF02 have metal screens with ¹/₄ inch by ¹/₄-inch (6 mm by 6 mm) openings and provide 37 square inches (0.02 m²) of net free opening to supply natural ventilation for under-floor ventilation. Flood Flaps® automatic FV models FFWF12, FFWF08, and FFWF05 have not been evaluated for use as openings for under-floor ventilation.

4.0 DESIGN AND INSTALLATION

Flood Flaps® automatic FVs are designed to be installed into walls of existing or new construction. Installation of the FVs must be in accordance with the manufacturer's instructions, the applicable code and this report. Flood Flaps® automatic FVs can be installed in wood, masonry and concrete walls up to a thickness of 12 inches (305 mm). In order to comply with the engineered opening design principle noted in Sections 2.7.2.2 and 2.7.3 of ASCE/SEI 24-14 (2021, 2018 and 2015 IBC and IRC) [Section 2.6.2.2 of ASCE/SEI 24-05 (2012 and 2009 IBC and IRC)], the Flood Flaps® FVs must be installed as follows:

- With a minimum of two openings on different sides of each enclosed area.
- With a minimum of one FV for every 220 squarefeet (20 m²) of enclosed area.
- Below the base flood elevation.
- With the bottom of the FV located a maximum of12 inches (305 mm) above grade.

5.0 CONDITIONS OF USE:

The Flood Flaps® automatic flood vents described in this report comply with, or are suitable alternatives to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

- 5.1 The Flood Flaps® automatic FVs must be installed in accordance with this report, the applicable code and the manufacturer's installation instructions. In the event of a conflict, the instructions in this report govern.
- **5.2** The Flood Flaps® automatic FVs must not be used in place of "breakaway walls" in coastal high hazard areas but are permitted for use in conjunction with breakaway walls in other areas.

6.0 EVIDENCE SUBMITTED

Data in accordance with the ICC-ES Acceptance Criteria for Mechanically Operated Flood Vents (AC364), dated August 2015 (editorially revised April 2021).

7.0 IDENTIFICATION

- 7.1 The ICC-ES mark of conformity, electronic labeling, or the evaluation report number (ICC-ES ESR-3560) along with the name, registered trademark, or registered logo of the report holder (Flood Flaps®) must be included in the product label.
- 7.2 In addition, the Flood Flaps® models described in this report are identified by a label bearing the model number.
- 7.3 The report holder's contact information is the following:

FLOOD FLAPS®, LLC
POST OFFICE BOX 1003
ISLE OF PALMS, SOUTH CAROLINA 29451
(843) 881-0190
www.floodflaps.com
info@floodflaps.com

TABLE 1—FLOOD FLAP AUTOMATIC FLOOD VENT MODEL SIZES

MODEL NUMBER	MODEL DESIGNATION	ROUGH OPENING (Width X Height) (inches)	VENT SIZE (W X H X D) (inches)	ENCLOSED AREA COVERAGE ² (ft ²)	NET FREE AREA OPENING ¹ (in ²)
FFWF12	Sealed Series	16 x 8	15 ⁵ / ₈ X 7 ³ / ₄ X 12	220	NA
FFNF12	Multi-Purpose	16 x 8	15 ⁵ / ₈ X 7 ³ / ₄ X 12	220	37
FFWF08	Sealed Series	16 x 8	15 ⁵ / ₈ x 7 ³ / ₄ x 8	220	NA
FFNF08	Multi-Purpose	16 x 8	15 ⁵ / ₈ x 7 ³ / ₄ x 8	220	37
FFWF05	Sealed Series	16 x 8	15 ⁵ / ₈ x 7 ³ / ₄ x 5	220	NA
FFNF05	Multi-Purpose	16 x 8	15 ⁵ / ₈ x 7 ³ / ₄ x 5	220	37

For Si: 1 inch = 25.4 mm; 1 f^2 = 0.093 m^2

¹For under-floor ventilation only.
²The enclosed coverage area in square feet for each model is equivalent to the performance of the same number of square inches of non-engineered openings.







FIGURE 1-FLOOD FLAPS® AUTOMATIC FLOOD VENT







FFWF12

FFNF08

FFNF05

FIGURE 2—FLOOD FLAPS® AUTOMATIC FLOOD VENT SERIES MODELS







12" DEPTH

8" DEPTH

5" DEPTH

FIGURE 3—FLOOD FLAPS® AUTOMATIC FLOOD VENTS MULTIPLE DEPTH OFFERINGS



ICC-ES Evaluation Report

ESR-3560 CBC and CRC Supplement

Reissued September 2023

This report is subject to renewal September 2024.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 08 00 00—OPENINGS

Section: 08 95 43—Vents/Foundation Flood Vents

REPORT HOLDER:

FLOOD FLAPS®, LLC

EVALUATION SUBJECT:

FLOOD FLAPS® AUTOMATIC FLOOD VENTS: MODELS FFWF12; FFNF12; FFWF08; FFNF08; FFWF05; FFNF05

1.0 REPORT PURPOSE AND SCOPE

Purpose:

The purpose of this evaluation report supplement is to indicate that Flood Flaps® automatic flood vents, described in ICC-ES evaluation report ESR-3560, has also been evaluated for compliance with the code(s) noted below.

Applicable code editions:

- 2022 California Building Code (CBC)
- 2022 California Residential Code (CRC)

For evaluation of applicable Chapters adopted by the California Office of Statewide Health Planning and Development (OSHPD) AKA: California Department of Health Care Access and Information (HCAI) and the Division of State Architect (DSA), see Sections 2.1.1 and 2.1.2 below.

2.0 CONCLUSIONS

2.1 CBC:

The Flood Flaps® automatic flood vents, described in Sections 2.0 through 7.0 of the evaluation report ESR-3560, comply with CBC Chapter 12, provided the design and installation are in accordance with the 2021 International Building Code® (IBC) provisions noted in the evaluation report and the additional requirements of CBC Chapters 12 and 16, as applicable.

- 2.1.1 OSHPD: The applicable OSHPD Sections and Chapters of the CBC are beyond the scope of this supplement.
- 2.1.2 DSA: The applicable DSA Sections and Chapters of the CBC are beyond the scope of this supplement.

2.2 CRC:

The Flood Flaps® automatic flood vents, described in Sections 2.0 through 7.0 of the evaluation report ESR-3560, comply with 2021 CRC, provided the design and installation are in accordance with the 2021 International Residential Code® (IRC) provisions noted in the evaluation report.

This supplement expires concurrently with the evaluation report, reissued September 2023.





ICC-ES Evaluation Report

ESR-3560 FBC Supplement

Reissued September 2023

This report is subject to renewal September 2024.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 08 00 00—OPENINGS

Section: 08 95 43-Vents/Foundation Flood Vents

REPORT HOLDER:

FLOOD FLAPS®, LLC

EVALUATION SUBJECT:

FLOOD FLAPS® AUTOMATIC FLOOD VENTS: MODELS FFWF12; FFNF12; FFWF08; FFNF08; FFWF05; FFNF05

1.0 REPORT PURPOSE AND SCOPE

Purpose:

The purpose of this evaluation report supplement is to indicate that Flood Flaps® automatic flood vents, described in ICC-ES evaluation report ESR-3560, have also been evaluated for compliance with the codes noted below.

Applicable code editions:

- 2023 and 2020 Florida Building Code—Building
- 2023 and 2020 Florida Building Code—Residential

2.0 CONCLUSIONS

The Flood Flaps® flood vents, described in Sections 2.0 through 7.0 of the evaluation report ESR-3560, comply with the *Florida Building Code—Building Code—*

Use of the Flood Flaps flood vents has also been found to be in compliance with the High-Velocity Hurricane Zone provisions of the Florida Building Code—Building and the Florida Building Code—Residential.

For products falling under Florida Rule 61G20-3, verification that the report holder's quality-assurance program is audited by a quality-assurance entity approved by the Florida Building Commission for the type of inspections being conducted is the responsibility of an approved validation entity (or the code official, when the report holder does not possess an approval by the Commission).

This supplement expires concurrently with the evaluation report, reissued September 2023.

