SITE DEVELOPMENT PLANS FOR

COMMERCIAL SPACE

POOLER, CHATHAM COUNTY, GEORGIA

Prepared for

COMBAT VETERANS, LLC

PROJECT DATA

107 GODLEY WAY POOLER, GEORGIA, 31322

PUD - PLANNED UNIT DEVELOPMENT

24HR CONTACT:

(912) 644-3223

COMMERCIAL / RETAIL


MPERVIOUS AREA:

PARKING SPACES REQUIRED:

PARKING SPACES PROVIDED:

THE OWNER MUST CERTIFY THAT ALL LAND DISTURBING AND DEVELOPMENT ACTIVITIES WILL BE COMPLETED IN ACCORDANCE WITH THE APPROVED STORMWATER MANAGEMENT DESIGN PLAN.

THE DESIGNER MUST CERTIFY THAT THE DESIGN MEETS THE REQUIREMENTS OF THE CITY OF POOLER AND THE LATEST EDITION OF THE COASTAL STORMWATER SUPPLEMENT TO THE GEORGIA STORMWATER MANAGEMENT MANUAL, AND ANY RELEVANT LOCAL ADDENDA.



VICINITY MAP




PROJECT LOCATION: 780 POOLER PARKWAY POOLER, CHATHAM COUNTY, GEORGIA EMC PROJECT# 20-0130 JULY 2023 REVISED JANUARY 2025



EMC ENGINEERING SERVICES, INC.

ENVIRONMENTAL- MARINE - CIVIL - SURVEY



	Sheet List Table
Sheet Number	Sheet Title
1	COVER
2	GENERAL NOTES
3	EXISTING CONDITIONS AND DEMOLITION PLAN
4	STAKING PLAN
5	UTILITY PLAN
6	PAVING, GRADING, AND DRAINAGE PLAN
7	STORM DRAINAGE PROFILE
8	INITIAL EROSION CONTROL PLAN
9	INTERMEDIATE EROSION CONTROL PLAN
10	FINAL EROSION CONTROL PLAN
11	LANDSCAPE PLAN
12	EROSION CONTROL NOTES
13	EROSION CONTROL NOTES
14	CONSTRUCTION DETAILS
15	CONSTRUCTION DETAILS
16	CONSTRUCTION DETAILS
17	CONSTRUCTION DETAILS
18	CONSTRUCTION DETAILS

UTILITY LOCATION DISCLAIMER


PERSONNEL. THE SURVEYOR MAKES NO GUARANTEE THAT THE UTILITIES SHOWN COMPRISE ALL SUCH UTILITIES IN THE AREA, EITHER IN SERVICE OR ABANDONED. THE EXACT LOCATION INDICATED, ALTHOUGH HE DOES CERTIFY THAT THEY ARE


REVISION	DESCRIPTION	DATE
1	REVISIONS PER CITY OF POOLER - INITIAL SUBMITTAL DATE 7/1/2021 - REVISIONS RECIEVED 7/21/2021	9/1/2021
2	REVISIONS PER CITY OF POOLER - RESUBMITTAL DATE 9/1/2021 - REVISIONS RECIEVED 10/6/2021	10/26/2021
3	REVISIONS PER CITY OF POOLER - RESUBMITTAL DATE 10/26/2021 - REVISIONS RECIEVED 11/4/2021	11/ /2021
4	REVISIONS PER CITY OF POOLER - FINAL COMMENTS	8/1/2023
5	OWNER REVISIONS	1/24/25
-	-	-
_	_	-



EMC ENGINEERING SERVICES, INC 10 CHATHAM CENTER SOUTH, SUITE 100

> PHONE: (912) 232-6533 savannah@emc-eng.com





EXISTING FEATURES LEGEND SYMBOLS OPEN TOP PIPE FOUND DRILL HOLE SET ANGLE IRON FOUND PK NAIL FOUND AXLE FOUND HUB FOUND PK NAIL SET BENCHMARK FOUND REBAR FOUND BENCHMARK SET HUB & TACK FOUND IRON REBAR SET CHOPS FOUND RAILROAD SPIKE FOUND CONCRETE MONUMENT FOUND RRSS RAILROAD SPIKE SET CONCRETE MONUMENT SET RIGHT/WAY MONUMENT FOUND IRON REBAR FOLING CONCRETE NAIL FOUND RWMS RIGHT/WAY MONUMENT SET CONCRETE NAIL SET TACK FOUND CONTROL POINT TACK SET X FOUND DRILL HOLE FOUND X-SETFLECTRIC CONTROL BOX BACKELOW PREVENTER TV MARKER FIRE DEPARTMENT CONNECTION TV PEDESTAL ELECTRIC METER ELECTRIC MANHOLE FIRE HYDRANT UNDERGROUND CABLE BOX FLECTRIC OUTLET FIBER OPTIC MARKER HOSE BIB ELECTRIC STUB OUT IRRIGATION CONTROL VALVE TELEPHONE BOOTH ELECTRIC TRANSFORMER IRRIGATION SPRINKLER HEAD TELEPHONE CABINET POST INDICATOR VALVE TELEPHONE LINE MARKER FLOOD LAMP TELEPHONE MANHOLE GROUND LIGHT GUY POLE REDUCED PRESSURE ZONE TELEPHONE PEDESTAL UNDERGROUND COMM BOX GUY WIRE ANCHOR WATER WELL WATER LINE MARKER GAS AIR RELEASE VALVE GAS METER POWER-LIGHT POLE WATER METER POWER POLE WATER MANHOLE GAS MANHOLF ELECTRIC MARKER WATER STUB OUT GAS MARKER CATCH BASIN GAS VALVE WATER VALVE CURR INLET FORCEMAIN AIR RELEASE VALVE GAS VENT PIPE DOUBLE WING CURB INLET PEDESTRIAN SIGNAL POLE FORCEMAIN LINE MARKER FLARED END SECTION SANITARY GREASE TRAP TRAFFIC SIGNAL CONTROL BOX GRATE INLET SANITARY SEWER CLEANOUT TRAFFIC SIGNAL MANHOLE HOODED GRATE INLET SANITARY SEWER MANHOLE TRAFFIC SIGNAL MARKER SANITARY SEWER STUB OUT JUNCTION BOX TRAFFIC SIGNAL POLE STORM SEWER CLEANOUT FENCE POST TRAFFIC SIGNAL STRAIN POLE STORM SEWER MANHOLE WHEELSTOP PARKING METER SINGLE WING CURB INLE POST/POLE BOREHOLE FOUND BILLBOARD ROOF DRAIN MONITORING WELL FOUND SINGLE POLE SIGN SAT DISH SATELLITE DISH SECURITY CAMERA POLE DOUBLE POLE SIGN STUB MBSTUR OUT MAII BOX 000 TRIPLE POLE SIGN AIR CONDITIONING UNIT WETLAND FLAG *BOLLARD*

PROPERTY LINE — — —		EASEMENT —				
ADJACENT PROPERTY — — —		BUILDING SETBACK —				
BUILDING		SANITARY SEWER —		— ss— -		- ss
BUILDING OVERHANG — — —		FORCEMAIN —		— FM — -		– FM —
DITCH CENTERLINE · <	· · <	STORM SEWER —		- —ST— -		-ST
WETLANDS — WET—	2/2 A/2	NATURAL GAS —		G		- G
CREEK CENTERLINE — — —		WATER LINE —		w		W
100-YEAR FLOODPLAIN — 100YR —		AERIAL TV —		—TV— —		
500-YEAR FLOODPLAIN — 500YR —		AERIAL FIBER OPTIC —		-F0		
100-YEAR FLOODWAY - NONNON		AERIAL ELECTRIC -	—E— —		−E— −	
MAJOR CONTOUR ————————————————————————————————————		AERIAL TRAFFIC SIGNAL —		—TS— —		
MINOR CONTOUR — — — — — — — — — — — — — — — — — — —		AERIAL TELEPHONE –	— ⊺ — —		−T— −	
WOODSLINE . YYYY	\\\\\\\	BURIED TV —		- —TV— -		-TV
ROADWAY CENTERLINE		BURIED FIBER OPTIC —		- —FO— -		-FO
PAVED ROADWAY		BURIED ELECTRIC —		E		-E
GRAVEL ROADWAY ————————————————————————————————————		BURIED TRAFFIC SIGNAL				
DIRT ROADWAY		BURIED TELEPHONE —		— т — -		-T
GUARDRAIL • • • • •	<u> </u>	SINGLE ROW SILT FENCE—	x	x -		- X
BARBWRE/HOGWRE X	— —X ——	DOUBLE ROW SILT FENCE	XX	XX		-XX
CHAINLINK FENCE ———————————————————————————————————	— —o ——	WOOD/IRON SHADOWBOX FENCE		[]		-[]

			SHADOWBUX FENCE							
	ABBREVIATIONS									
BFE	BASE FLOOD ELEVATION	HDPE	HIGH DENSITY POLYETHYLENE	RCB	CONCRETE BOX CULVERT					
CMP	CORRUGATED METAL PIPE	HDW	HEADWALL	RCP	REINFORCED CONCRETE PIPE					
CPP	CORRUGATED PLASTIC PIPE	HWL	HIGH WATER LEVEL	THR	THROAT ELEVATION					
DIP	DUCTILE IRON PIPE	IE/INV	INVERT ELEVATION	VCP	VITRIFIED CLAY PIPE					
FFE	FINISHED FLOOR ELEVATION	L WL	LOW WATER LEVEL	VL T	VAULT					
FRD	FRENCH DRAIN	PVC	POLYVINYL CHLORIDE PIPE							

LOT DRAINAGE SHALL BE FROM THE REAR TO THE FRONT OF LOTS; 0.5% GRADE MINIMUM. EXCEPTIONS WILL BE CONSIDERED.

SIDE LOT DRAINAGE SHALL BE PIPED; DITCHES ON SIDE LOT LINES ARE NOT PERMITTED. EXCEPTIONS WILL BE CONSIDERED. MINIMUM LOT ELEVATION: FINISHED FLOOR ELEVATIONS SHALL BE AT LEAST ONE FOOT ABOVE THE LEVEL OF THE IOC-YEAR FLOOD. THE

THE CITY WILL NOT ACCEPT DETENTION AREAS FOR MAINTENANCE OR OWNERSHIP.

ENTIRE LOT SHALL BE PROPERLY DRAINED.

IT WILL BE THE RESPONSIBILITY OF THE CONTRACTOR TO INSURE THAT ALL REQUIRED PERMITS ARE OBTAINED PRIOR TO THE COMMENCEMENT OF CONSTRUCTION.

ALL CONSTRUCTION SHALL BE PERFORMED IN ACCORDANCE WITH THE CITY OF POOLER SPECIFICATIONS. IN CASE OF CONFLICT BETWEEN THESE PLANS AND THE CITY OF POOLER'S ORDINANCES, STANDARDS, SPECIFICATIONS OR DETAILS, THE CITY OF POOLER STANDARDS ARE TO TAKE PRECEDENCE

PRIOR TO INSTALLATION OF ANY UTILITY LINES. THE CONTRACTOR SHALL GIVE THE UTILITY COMPANIES THREE (3) WORKING DAYS NOTICE TO ALLOW TIME FOR EXISTING UTILITIES TO BE STAKED, BEFORE CALLING (811) THE CONTRACTOR SHALL HAVE THE FOLLOWING INFORMATION READY: COUNTY, TOWN, LOCATION, NEAREST STREET INTERSECTIONS, TYPE OF WORK (SEWER, WATER, PAVING FTC.) YOUR COMPANY NAME TELEPHONE NUMBER OWNER'S NAME DATE AND TIME YOU EXPECT TO COMMENCE CONSTRUCTION, AND WHERE AND HOW YOU CAN BE REACHED AND THE BEST TIME TO CONTACT YOU. THE CONTRACTOR SHALL EXERCISE CAUTION WHEN CROSSING AN UNDERGROUND UTILITY, WHETHER SHOWN ON THE PLAN OR LOCATED BY THE UTILITY COMPANY ALL LITH ITIES WHICH INTERFERE WITH THE PROPOSED CONSTRUCTION SHALL BE RELOCATED BY THE RESPECTIVE UTILITY COMPANIES, AND THE CONTRACTOR SHALL COOPERATE WITH THEM DURING RELOCATION OPERATIONS. THE CONTRACTOR SHALL NOTIFY THE ENGINEER OF ANY VARIANCES PRIOR TO COMMENCEMENT OF WORK OR PURCHASING ANY MATERIALS.

ALL KNOWN UTILITY FACILITIES ARE SHOWN SCHEMATICALLY ON THE PLANS AND ARE NOT NECESSARILY ACCURATE AS TO PLAN OR ELEVATION LITHLITY FACILITIES SUCH AS SERVICE LINES OR LINKNOWN FACILITIES NOT SHOWN ON THE PLANS WILL NOT RELIEVE THE CONTRACTOR OF HIS RESPONSIBILITIES, EXCEPT AS NOTED BELOW. THE CONTRACTOR WILL NOT BE RESPONSIBLE FOR THE COST OF REPAIRS TO DAMAGED UTILITY FACILITIES OTHER THAN SERVICE LINES FROM STREET MAINS TO ABUTTING PROPERTY WHEN SUCH FACILITIES ARE NOT SHOWN ON THE PLANS AND THEIR EXISTENCE IS UNKNOWN TO THE CONTRACTOR PRIOR TO THE DAMAGES OCCURRING PROVIDING THE ENGINEER DETERMINES THE CONTRACTOR HAS OTHERWISE FULLY COMPLIED WITH THE

IT IS THE OBLIGATION OF THE CONTRACTOR TO MAKE HIS OWN INTERPRETATION OF ALL SURFACE AND SUBSURFACE DATA AS TO THE NATURE AND EXTENT OF THE MATERIALS TO BE EXCAVATED. THE INFORMATION SHOWN ON THESE PLANS AND SPECIFICATIONS DOES

NOT IN ANY WAY GUARANTEE THE AMOUNT OR NATURE OF THE MATERIAL WHICH MAY BE ENCOUNTERED.

ALL REINFORCED CONCRETE PIPE (RCP) SHALL CONFORM TO ASTM C76, CLASS III. MINIMUM PIPE DIAMETER SHALL BE 15". PIPE JOINTS SHALL BE MADE BY USE OF A CONTINUOUS TYPE II OR III RUBBER GASKET CONFORMING TO THE REQUIREMENTS OF ASTM

FILL SHALL CONSIST OF SUITABLE MATERIALS WHICH ARE GENERALLY COMPOSED OF SANDS, CLAY-SAND MIXTURES, AND SILT-SAND MIXTURES AND ARE FREE OF ROOTS, TRASH, AND OTHER DELETERIOUS MATERIAL. CLAYS, SILTS, AND ORGANIC SOILS SHALL BE

THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND FURNISHING THE BORROW MATERIAL NECESSARY FOR THE CONSTRUCTION OF THIS PROJECT. BORROW MATERIAL SHALL BE CAPABLE OF BEING SHAPED AND COMPACTED TO THE REQUIRED

DURING CONSTRUCTION IN THE AREA OF AN INTERSECTION, WORK WILL BE PERFORMED IN SUCH A MANNER AS TO PERMIT TRAFFIC TO OPERATE WITH THE LEAST AMOUNT OF INCONVENIENCE POSSIBLE. ADDITIONAL CHANNELIZATION AND SIGNAGE SHALL BE INSTALLED, AS DIRECTED BY THE ENGINEER, TO ALLOW TRAFFIC TO FLOW AS FREELY AS POSSIBLE. WHEN AN INTERSECTION IS INOPERABLE, FLAGGERS WILL BE UTILIZED TO CONTROL TRAFFIC. ALL TRAFFIC CONTROL DEVICES AND METHODS SHALL BE PER THE

10. A COMPLETE PERMIT SET OF PLANS MUST BE KEPT ON SITE AT ALL TIMES.

PROTECTION OF EXCAVATED AREAS: - TEMPORARY FENCING SHALL BE USED AROUND OPEN EXCAVATIONS AT ALL TIMES, EXCEPT AS 9. NECESSARY FOR IMMEDIATE CONSTRUCTION. WHEN WORK IS NOT IN PROGRESS, FENCING SHALL ENCLOSE EXCAVATED AREAS. UTILITY TRENCHES SHALL BE BACKFILLED TO GRADE AT THE END OF THE DAY, ALLOWING FOR A MAXIMUM OF 10' (FENCE-PROTECTED) TRENCH TO REMAIN OPEN.

12. THE CONTRACTOR SHALL FIELD VERIFY ALL ELEVATIONS PRIOR TO CONSTRUCTION.

LABORATORY COMPACTION, STABILITY AND DENSITY TESTS ARE REQUIRED FOR THE PAVEMENT WITH COMPRESSION FOR THE 11. CONCRETE CURB AND GUTTER.

CONSTRUCTION WILL BE PERFORMED UNDER THE SUPERVISION OF AN ENGINEER REGISTERED IN THE STATE OF GEORGIA

THERMOPLASTIC PAVEMENT MARKINGS ARE REQUIRED WITHIN RIGHT OF WAY. ALL ROAD SIGNAGE AND PAVEMENT MARKINGS SHALL

BE IN ACCORDANCE WITH MUTCH SPECIFICATIONS LATEST EDITION SELECT FILL SHALL BE USED IN ALL DRIVEWAYS TO BE LOCATED IN THE CITY'S R/W AND THE FILL SHALL BE COMPACTED TO 100%

STANDARD PROCTOR (ASTM D 698)

TRAFFIC SIGNS INSTALLED INSIDE THE PUBLIC R/W MUST HAVE HIGH INTENSITY OR DIAMOND GRADE SHEETING.

GDOT PERMIT IS REQUIRED IF ANY WORK IS PROPOSED IN A STATE OR US ROUTE. A COPY OF THE GEORGIA DOT ENCROACHMENT PERMIT APPROVAL PRIOR TO OBTAINING A LAND DISTURBANCE PERMIT

AT LEAST TWO BENCHMARKS SHALL BE ESTABLISHED WITHIN A SUBDIVISION. SUCH BENCHMARKS SHALL BE AT OPPOSITE CORNERS OF THE 16. UNDERGROUND MARKING TAPE SHALL BE INSTALLED OVER ALL WATER MAINS (18" BELOW GRADE) PROPERTY BEING SUBDIVIDED.

GREENBELT REQUIRED AS A BUFFER BETWEEN INCOMPATIBLE ZONINGS.

MINIMUM STREET PROFILE GRADE IS 0.3%.

PAVEMENT REQUIREMENTS: 8.0 INCHES CRUSHED STONE BASE AND 1.5 INCHES ASPHALT WEARING SURFACE IN ACCORDANCE WITH CITY OF POOLER STANDARD DETAILS

ALL PAVEMENT MARKINGS AND OTHER TRAFFIC CONTROL ITEMS SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE MUTCD ON BOTH PUBLIC STREETS AND PRIVATE STREETS THAT ARE "OPEN TO PUBLIC TRAVEL".

IN CASE OF CONFLICT BETWEEN THESE PLANS AND THE CITY OF POOLER'S ORDINANCES, STANDARDS, SPECIFICATIONS OR DETAILS, THE CITY OF

LABORATORY COMPACTION, STABILITY AND DENSITY TESTS ARE REQUIRED FOR THE PAVEMENT WITH COMPRESSION FOR THE CONCRETE CURB

26. CONSTRUCTION WILL BE PERFORMED UNDER THE SUPERVISION OF A REGISTERED ENGINEER.

ALL ROAD SIGNAGE AND PAVEMENT MARKINGS SHALL BE IN ACCORDANCE WITH MUTCD SPECIFICATIONS

THERMOPLASTIC PAVEMENT MARKINGS ARE REQUIRED WITHIN THE RIGHT OF WAY.

SELECT FILL SHALL BE USE IN ALL ROADS TO BE DEDICATED TO THE CITY

ROAD FILL SHALL BE COMPACTED TO 100% STANDARD PROCTOR (ASTM D 698)

STREET NAME SIGNS SHALL BE PROVIDED BY THE DEVELOPER.

APPROVED STORMWATER MANAGEMENT DESIGN PLAN.

THE OWNER MUST CERTIFY THAT ALL LAND DISTURBING AND DEVELOPMENT ACTIVITIES WILL BE COMPLETED IN ACCORDANCE WITH THE

THE DESIGNER MUST CERTIFY THAT THE DESIGN MEETS THE REQUIREMENTS OF THE CITY OF POOLER AND THE LATEST EDITION OF THE COASTAL 8.

STORMWATER SUPPLEMENT TO THE GEORGIA STORMWATER MANAGEMENT MANUAL, AND ANY RELEVANT LOCAL ADDENDA. 34. EXCAVATIONS

a. NO PERSON SHALL REMOVE, DIG, EXCAVATE, BORE UNDER, TRENCH, PLOW OR DESTROY ANY PORTION OF ANY SIDEWALK, PUBLIC WAY, RIGHT-OF-WAY AND/OR ROAD, FOR ANY PURPOSE OTHER THAN FOR EMERGENCY UTILITY REPAIRS OR LAYING WATER MAINS, STORM DRAINS OR SANITARY SEWER UNDER THE SUPERVISION AND CONTROL OF THE CITY, WITHOUT FIRST OBTAINING A PERMIT FROM THE PERMITS SHALL BE APPLIED FOR NOT LESS THAN 72 HOURS, NOT INCLUDING WEEKENDS AND/OR HOLIDAYS, BEFORE ANY EXCAVATION

IS SCHEDULED TO BEGIN. THE COST OF OBTAINING A PERMIT SHALL BE AS SET FORTH IN THE SCHEDULE OF FEES AND CHARGES. PERMITS CAN BE OBTAINED FROM THE PUBLIC WORKS DEPARTMENT AND/OR THE CITY DESIGNEE

IF THERE IS ANY CONFLICT IN THE INTERPRETATION OF REGULATIONS REGARDING EXCAVATION OF UTILITIES, THE INTERPRETATION OF THE CITY OF POOLER SHALL GOVERN.

RECONSTRUCTION AND CLOSEOUT REQUIREMENTS

ALL PROJECTS CONSTRUCTED WITHIN THE CITY LIMITS OF POOLER AND/OR CONNECTING TO THE CITY OF POOLER WATER AND SEWER SYSTEM MUST BE CONSTRUCTED IN ACCORDANCE WITH THE CITY OF POOLER STANDARD SPECIFICATIONS. NO EXCEPTIONS SHALL BE MADE FOR PRIVATELY MAINTAINED SYSTEMS.

ALL PROJECTS SHALL BE TIED TO AND SHALL BE COMPLETED ON THE NAVD 1988 VERTICAL DATUM AND THE NAD 83 STATE PLANE COORDINATES HORINZONTAL DATUM AND SHALL BE BASED ON US SURVEY FEET.

PRIOR TO BEGINNING OF CONSTRUCTION A PRE-CONSTRUCTION CONFERENCE WILL BE SCHEDULED AND SHALL BE

GENERAL:

THE PIPES, FITTINGS, VALVES AND OTHER ACCESSORIES SHALL, UNLESS OTHERWISE DIRECTED, BE UNLOADED AT THE POINT OF DELIVERY, AND STORED WHERE THEY WILL BE PROTECTED AND WILL NOT BE HAZARDOUS TO TRAFFIC. THEY SHALL AT ALL TIMES BE HANDLED WITH CARE TO AVOID DAMAGE. THE INTERIOR OF ALL PIPE, FITTINGS AND OTHER ACCESSORIES SHALL BE KEPT FREE FROM ALL FOREIGN MATTER AT ALL TIMES.

ANY DEFECTIVE, DAMAGED, OR UNSOUND PIPES SHALL BE REJECTED. ALL FOREIGN MATTER SHALL BE REMOVED FROM THE INSIDE OF THE PIPE BEFORE IT IS LOWERED INTO ITS POSITION IN THE TRENCH AND IT SHALL BE KEPT CLEAN BY APPROVED MEANS DURING AND AFTER LAYING. CARE SHALL BE TAKEN TO PREVENT FOREIGN MATTER FROM ENTERING THE JOINT SPACE AT TIMES WHEN PIPE LAYING IS NOT IN PROGRESS, THE OPEN ENDS OF THE PIPE SHALL BE PLUGGED OR CAPPED BY APPROVED MEANS TO FORM A WATER TIGHT SEAL. NO TRENCH WATER SHALL BE PERMITTED TO ENTER THE PIPE.

ALL WET TAPS SHALL INCLUDE TAPPING SADDLES, SLEEVES, VALVES AND VALVE BOXES OR MANHOLES AS NOTED ON UTILITIES SHEET. ALL EXCAVATION, PROVIDING AND INSTALLING OF TAPPING SLEEVE, TAPPING VALVE IN A MANHOLE, THRUST RESISTANCE BLOCKS/TIE-RODS/MEGALUGS, BACKFILL, COMPRESSOR, MANPOWER, ETC. WILL BE PROVIDED BY THE CONTRACTOR. THE DEVELOPER/CONTRACTOR IS TO COORDINATE THE WET TAP WITH THE CITY OF POOLER PUBLIC WORKS

TAPPING SLEEVES SHALL BE MECHANICAL JOINT TYPE, MUELLER NO. H-615, CLOW F-5205, OR APPROVED EQUAL. TAPPING VALVES SHALL BE MECHANICAL JOINT TYPE GATE VALVES, MUELLER NO 667, CLOW F-5093, OR APPROVED EQUAL

GATE VALVES SHALL BE AMERICAN, WATEROUS, OR EQUAL AND SHALL BE FURNISHED WITH STANDARD OPERATING NUTS. BALL VALVES 2" AND SMALLER SHALL BE DESIGNED FOR A WORKING PRESSURE OF NOT LESS THAN 300 PSI, DOMESTIC MADE BRASS, AND SHALL CONFORM TO AWWA C 800-89.

FIRE HYDRANTS SHALL BE 5-1/4" MINIMUM AMERICAN DARLING, MUELLER, M&H, OR APPROVED EQUAL AND SHALL CONFORM TO AWWA C502.

DISINFECTION AND FLUSHING WATER MAINS: CONTRACTOR SHALL NOTIFY ENGINEER 48 HOURS IN ADVANCE OF ANY DISINFECTION AND FLUSHING OF NEWLY CONSTRUCTED WATER MAINS. FLUSHING WATER AND SUPER CHLORINATED WATER WILL BE DISPOSED OF BY A METHOD APPROVED BY THE ENGINEER. CHLORINATED DISINFECTED WATER SHALL NOT BE DISCHARGED INTO THE EXISTING OR PROPOSED STORM DRAINAGE SYSTEMS.

FLUSHING WATER MAY BE DISCHARGED INTO THE SANITARY SEWER SYSTEM AFTER BEING FILTERED OF LARGE SOLIDS AND SEDIMENT LINDER THE SUPERVISION OF THE ENGINEER

FLUSHING PROCEDURES SHALL INCLUDE OPEN-ENDED FLUSHING IN ORDER TO INSURE THE LINE IS CLEAR. FLUSH NEW PIPE LINES UNTIL THE WATER RUNS CLEAR AT THE END OF ALL MAINS AND LATERALS. THIS SHALL BE DONE

AFTER PRESSURE TEST AND BEFORE DISINFECTION. THE LINES SHALL BE FLUSHED USING A METHOD ACCEPTABLE TO THE CITY PRIOR TO CONNECTION TO THE WATER SYSTEM. LINES SHALL BE FLUSHED FOR 30 MINUTES AT A VELOCITY SUFFICIENT TO PURGE THE LINES OF ANY

FOREIGN MATTER CLEAN THE INTERIOR OF ALL PIPE BY BRUSHING, SWABBING, OR WASHING OUT ALL DIRT BEFORE LAYING

ALL WATER USED FOR CONSTRUCTION SHALL BE METERED THROUGH AN APPROVED BACK FLOW PREVENTION DEVICE AND FIRE

PRIOR TO CONNECTING TO ANY EXISTING WATER MAINS, RELISE MAINS, OR SANITARY SEWER LINES AND PRIOR TO DIGGING FOR PROPOSED CONSTRUCTION THE CONTRACTOR SHALL CONTACT THE RESPECTIVE UTILITY OWNER A MINIMUM OF SEVENTY-TWO (72) HOURS PRIOR TO DIGGING

10. AN APPROVED WATER SUPPLY FOR FIRE PROTECTION, EITHER TEMPORARY OR PERMANENT, SHALL BE MADE AVAILABLE AS

NATIONAL STANDARDS INSTITUTE / NATIONAL SANITARY FOUNDATION STANDARD 61 (ANSI/NSF STANDARD 61)

SOON AS COMBUSTIBLE MATERIAL ARRIVES ON THE SITE. ALL MATERIALS USED AND THAT COME INTO CONTACT WITH DRINKING WATER DURING ITS DISTRIBUTION SHALL NOT ADVERSELY AFFECT DRINKING WATER QUALITY AND PUBLIC HEALTH AND MUST BE CERTIFIED FOR CONFORMANCE WITH AMERICAN

MAINTAIN A MINIMUM OF 36" OF COVER FOR ALL MAINS 12" AND SMALLER. A MAXIMUM COVER OF 60" FROM FINISHED GRADE SHALL BE USED UNLESS APPROVED TO AVOID CONFLICT. IF THE COVER IS LESS THAN 36". DUCTILE IRON PIPE SHALL BE USED.

ALL PHASES OF CONSTRUCTION OF THE WATER SYSTEM SHALL COMPLY WITH THE GA EPD RULES FOR SAFE DRINKING WATER, CHAPTER 391-3-5 AND THE LATEST EDITION OF THE EPD MINIMUM STANDARDS FOR PUBLIC WATER SYSTEMS.

MAXIMUM JOINT DEFLECTION AND BENDING OF PVC PIPE SHALL NOT EXCEED MANUFACTURER'S SPECIFICATIONS AND

A #12 GAUGE SOLID COPPER TRACING WIRE SHALL BE INSTALLED ON ALL WATER MAINS, WATER LATERALS, FIRE HYDRANTS, POST HYDRANTS, AND/OR BLOW OFFS AND ALONG ALL SANITARY SEWER LINES, LATERALS, AND FORCE MAINS.

UTILITIES SHALL NOT BE PLACED LONGITUDINALLY UNDER STREET PAVEMENT

MAINTAIN A MINIMUM OF 10' SEPARATION HORIZONTAL AND 18" VERTICAL BETWEEN WATER & SEWER LINES.

WATER MAINS MUST BE DIP WHEN CROSSING STORM OR SEWER MAINS

20. ALL WATER AND SEWER LINES RUNNING UNDER STREETS/SIDEWALKS SHALL BE SLEEVED. ALL PUBLICLY OWNED UTILITIES SHALL BE INSTALLED IN THE ROAD RIGHTS-OF-WAY OR APPROVED ACCESS EASEMENT:

SANITARY SEWER, WATER MAINS, SERVICE LATERALS OR OTHER PUBLICLY OWNED UTILITIES SHALL NOT BE INSTALLED BEHIND OR BETWEEN

LOTS WITHOUT THE EXPRESS APPROVAL OF THE CITY OF POOLER. IF ALLOWED THE UTILITY WILL NEED TO BE IN A PROPER EASEMENT.

ALL PUBLIC FIRE HYDRANTS SHALL BE PAINTED YELLOW.

RESIDENTIAL WATER LATERALS: 1" DIAMETER MINIMUM.

RESIDENTIAL WATER LATERALS SHALL BE INSTALLED NO MORE THAN 5' FEET FROM THE PROPERTY CORNER.

THE WATER MAINS AT THE CUL-DE-SAC SHALL BE INSTALLED AROUND THE CUL-DE-SAC THEREBY ELIMINATING THE LATERALS FROM BEING

CUT-OFF VALVES WILL BE LOCATED AT ALL TEES WHERE LINES ARE TWO INCHES OR LARGER

ALL GATE VALVES 4" OR LARGER THAT ARE INSTALLED ON A TRANSMISSION LINE SHALL BE INSTALLED IN A MANHOLE. ALL GATE VALVES AT

THE ENTRANCE OF A SUBDIVISION THAT TIE INTO A TRANSMISSION LINE SHALL BE INSTALLED IN A MANHOLE. ALL OTHER GATE VALVES CAN BE INSTALLED IN A CAST IRON VALVE BOX WITH A CONCRETE COLLAR AND CONCRETE VALVE MARKER POSTS.

ALL VALVES SHALL HAVE A CONCRETE MONUMENT WITH 'I W/VALVE" INSCRIBED ON TWO SIDES OF THE MONUMENT, INSTALLED NO MORE THAN 6" AWAY FROM THE VALVE.

ALL METER CONNECTION POINTS MUST HAVE AN APPROVED, REDUCED PRESSURE BACKFLOW DEVICE. THIS INCLUDES FIRE LINES,

MAINTAIN A MINIMUM OF 3 FEET OF COVER.

10. SERVICE LATERALS UNDER ROADS ARE TO BE SLEEVED AND AT LEAST 30" BENEATH THE ROAD SURFACE.

PIPE MATERIAL: FOR LINE SIZE < 4" POLYETHYLENE PIPE, 200 PSI, SIDR-7CTS FOR LINE SIZE 4" - 12" PVC C900 DR 18

FOR LINE SIZE > 12" DIP IS REQUIRED. ANSI / AWWA C151 A21.51 AND THICKNESS ACCORDING TO ANSI / AWWA C150 A21.50 FOR PRESSURE CLASS 250. FLANGE PIPE OR VICTAULIC GROOVED PIPE SHALL BE PRESSURE CLASS 350

SANITARY SEWER:

SANITARY MANHOLES SHALL NOT EXCEED 350-FOOT SPACING

PIPE DIAMETER SHALL BE A MINIMUM OF 8 INCHES.

MINIMUM SIZE OF SANITARY LATERAL IS 4 INCHES.

LATERALS SHALL CONNECT DIRECTLY TO THE MANHOLE WHEN POSSIBLE, ENTERING AT AN ANGLE OF AT LEAST 90 DEGREES TO THE

RESIDENTIAL SEWER LATERALS SHALL BE INSTALLED WITHIN 15 FEET OF THE PROPERTY CORNER.

CLEANOUTS SHALL BE PROVIDED EVERY 100' AND AT THE BENDS. CLEANOUTS LOCATED WITHIN THE PAVEMENT SHALL BE TRAFFIC RATED.

MANHOLES SHALL NOT BE PLACED IN SIDEWALKS UNLESS APPROVED BY THE CITY OF POOLER.

SDR 26 PVC SEWER PIPE MEETING THE REQUIREMENTS OF ASTM D3034 FOR PIPES 15" AND SMALLER AND ASTM F679 FOR 18" AND LARGER.

DROP MANHOLES ARE REQUIRED WHEN THE 'INVERT IN' IS 2.0 FEET OR MORE ABOVE THE 'INVERT OUT'. THE MH MUST BE A 6' DIAMETEI PRECAST MH AND CONFORM TO ASTM C478. THE DROP PIPE SHALL BE THE SAME SIZE AS THE INFLUENT PIPE. ALL HARDWARE ON DUCTILE

0.40% 0.10% 0.28% 0.08% 0.22% 0.07% 14" 0.17% 30" 0.06% 0.15% 0.05%

36"

42"

0.05%

0.14%


0.12%





PROJECT NO.: 20-0130 DRAWN BY: MRK **DESIGNED BY:** MRK SURVEYED BY: BREWER SURVEY DATE: 2018 CHECKED BY: ABM SCALE: DATE:


JANUARY 202 SHEET


ATTENDED BY THE ENGINEER OF RECORD OR OTHER OWNER'S REPRESENTATIVES, THE CONTRACTOR, AND CITY SANITARY SEWER CLEANOUTS SHALL BE FLOOD PROOFED AND DESIGNED TO PREVENT INFILTRATION OF FLOOD WATERS INTO THE SYSTEM. USE WATERTIGHT MANHOLE RINGS AND COVERS WITHIN OR BELOW BASE FLOOD ELEVATION + 1'. RECORD DRAWINGS OF THE APPROVED CONSTRUCTION PLANS IN THE FOLLOWING FORMAT SHALL BE DELIVERED TO THE CITY BY THE OWNER'S REPRESENTATIVE IN THE REQUIRED COORDINATE SYSTEM. a. (1) SET ON REPRODUCIBLE MYLAR b. (2) SETS ON BOND GREASE TRAP IS REQUIRED FOR RESTAURANTS / EATING ESTABLISHMENTS (ANY ESTABLISHMENT WITH KITCHEN FACILITIES) WITH A c. (1) COMPLETE SET OF DIGITAL RECORD DRAWINGS ON AUTOCAD FILE AND PDF SAMPLING MH ON THE EFFLUENT SIDE BEFORE THE SANITARY LINE FROM THE BUILDING ENTERS THE LINE. MH TO BE A MINIMUM OF 18 INCHES IN DIAMETER. (1) ORIGINAL LETTER, SIGNED AND SEALED BY A PROFESSIONAL ENGINEER REGISTERED IN THE STATE OF GEORGIA, CERTIFYING THE PROJECT HAS BEEN CONSTRUCTED IN ACCORDANCE WITH THE APPROVED PLANS AND SPECIFICATIONS DIP MANUFACTURED IN ACCORDANCE WITH ANSI A21.51 WITH THICKNESS ACCORDING TO ANSI A21.50. 2. GREASE TRAPS ARE TO BE SIZED BASED ON THE SIZE AND USE TYPE OF THE ESTABLISHMENT THEY ARE SERVING. SHALL BE SUBMITTED TO THE CITY. MAINTAIN A MINIMUM COVER OF 3 FEET. (3) COPIES OF ALL WARRANTIES, BONDS, AND OPERATION MANUALS SHALL BE SUBMITTED TO THE CITY. STORM DRAIN PIPE BENEATH CITY MAINTAINED STREETS SHALL BE A MINIMUM OF 18 INCHES IN DIAMETER AND SHALL BE RCP 6. (3) COPIES OF RECORDED PLATS SHOWING ALL REQUIRED ROW AND.OR EASEMENTS FOR PUBLIC AND/OR PRIVATE IRON PIPING ASSOCIATED WITH DROP MANHOLES MUST BE STAINLESS STEEL. STREETS, DRAINAGE, UTILITIES, ANF/OR FACILITIES SHALL BE SUBMITTED TO THE CITY. STORM SIDE-DRAIN UNDER DRIVEWAYS AND WALKWAYS SHALL BE 15 INCH MINIMUM. PLASTIC CULVERTS ARE ACCEPTABLE BUT SHALL HAVE CONCRETE HEADWALLS TO PROTECT THE PIPE ENDS. SANITARY SEWER LINE - MINIMUM SLOPE























FOR THE SAMPLING OF THE RECEIVING WATER(S) OR THE SAMPLING OF THE STORM WATER OUTFALLS AND THAT THE DESIGNED

SYSTEM OF BEST MANAGEMENT PRACTICES AND SAMPLING METHODS IS EXPECTED TO MEET THE REQUIREMENTS CONTAINED IN

THE GENERAL NPDES PERMIT NO. GAR 100001.

GSWCC LEVEL II CERTIFIED DESIGN PROFESSIONAL

YES 28. DESCRIPTION OF THE PRACTICES THAT WILL BE USED TO REDUCE THE POLLUTANTS IN STORM WATER DISCHARGES.*

HAZARDOUS WASTE - ALL HAZARDOUS WASTE MATERIALS WILL BE DISPOSED OF IN THE MANNER SPECIFIED BY LOCAL, STATE, AND/OR FEDERAL REGULATIONS AND BY THE MANUFACTURER OF SUCH PRODUCTS. THE JOB SITE SUPERINTENDENT, WHO WILL ALSO BE RESPONSIBLE FOR SEEING THAT THESE PRACTICES ARE FOLLOWED, WILL INSTRUCT SITE PERSONNEL IN THESE PRACTICES. MATERIAL SAFETY DATA SHEETS (MSDS'S) FOR EACH SUBSTANCE WITH HAZARDOUS PROPERTIES THAT IS USED ON THE JOB SITE WILL BE OBTAINED AND USED FOR THE PROPER MANAGEMENT OF POTENTIAL WASTES THAT MAY RESULT FROM THESE PRODUCTS. AN MSDS WILL BE POSTED IN THE IMMEDIATE AREA WHERE SUCH PRODUCT IS SORTED AND/OR USED AND ANOTHER COPY OF EACH MSDS WILL BE MAINTAINED IN THE ESPCP FILE AT THE JOB SITE CONSTRUCTION TRAILER OFFICE. EACH EMPLOYEE WHO MUST HANDLE A SUBSTANCE WITH HAZARDOUS PROPERTIES WILL BE INSTRUCTED ON THE USE OF MSDS SHEETS AND THE SPECIFIC INFORMATION IN THE APPLICABLE MSDS FOR THE PRODUCT HE/SHE IS USING PARTICULARLY REGARDING SPILL CONTROL TECHNIQUES.

THE CONTRACTOR WILL IMPLEMENT THE SPILL PREVENTION CONTROL AND COUNTERMEASURES (SCCC) PLAN FOUND WITHIN THE ESPCP AND WILL TRAIN ALL PERSONNEL IN THE PROPER CLEANUP AND HANDLING OF SPILLED MATERIALS. NO SPILLED HAZARDOUS MATERIALS OR HAZARDOUS WASTES WILL BE ALLOWED TO COME IN CONTACT WITH STORM WATER DISCHARGES. IF SUCH CONTACT OCCURS, THE STORM WATER DISCHARGE WILL BE CONTAINED ON SITE UNTIL APPROPRIATE MEASURES IN COMPLIANCE WITH STATE AND FEDERAL REGULATIONS ARE TAKEN TO DISPOSE OF SUCH CONTAMINATED STORMWATER. IT SHALL BE THE RESPONSIBILITY OF THE JOB SITE SUPERINTENDENT TO PROPERLY TRAIN ALL PERSONNEL IN THE USE OF THE SPCC PLAN.

SANITARY WASTES: A MINIMUM OF ONE PORTABLE SANITARY UNIT WILL BE PROVIDED FOR EVERY TEN (10) WORKERS ON THE SITE. ALL SANITARY WASTE UNITS WILL BE COLLECTED FROM THE PORTABLE UNITS A MINIMUM OF ONE TIME PER WEEK BY A LICENSED PORTABLE FACILITY PROVIDER IN COMPLETE COMPLIANCE WITH LOCAL AND STATE REGULATIONS.

ALL SANITARY WASTE UNITS WILL BE LOCATED IN AN AREA WHERE THE LIKELIHOOD OF THE UNIT CONTRIBUTING TO STORM WATER DISCHARGE IS NEGLIGIBLE. ADDITIONAL CONTAINMENT BMP'S MUST BE IMPLEMENTED, SUCH AS GRAVEL BAGS OR SPECIALLY DESIGNED PLASTIC SKID CONTAINERS AROUND THE BASE, TO PREVENT WASTES FROM CONTRIBUTING TO STORM WATER DISCHARGES. THE LOCATION OF SANITARY WASTE UNITS MUST BE IDENTIFIED ON THE EROSION CONTROL PLAN BY THE CONTRACTOR ONCE THE LOCATIONS HAVE BEEN DETERMINED.

FERTILIZER/HERBICIDE - THESE PRODUCTS WILL BE APPLIED AT RATES THAT DO NOT EXCEED THE MANUFACTURER'S SPEC. OR ABOVE THE GUIDELINES SET FORTH IN THE CROP ESTABLISHMENT OR IN THE GSWCC MANUAL FOR EROSION AND SEDIMENT CONTROL IN GA. ANY STORAGE OF THESE MATERIALS WILL BE UNDER ROOF IN SEALED CONTAINERS.

PAINTS/FINISHES/SOLVENTS - ALL PRODUCTS WILL BE STORED IN TIGHTLY SEALED ORIGINAL CONTAINERS WHEN NOT IN USE. EXCESS PRODUCT WILL NOT BE DISCHARGED TO THE STORM WATER COLLECTION SYSTEM. EXCESS PRODUCT, MATERIALS USED WITH THESE PRODUCTS AND PRODUCT CONTAINERS WILL BE DISPOSED OF ACCORDING TO MANUFACTURER'S SPECIFICATIONS AND RECOMMENDATIONS.

BUILDING MATERIALS - NO BUILDING OR CONSTRUCTION MATERIALS WILL BE BURIED OR DISPOSED OF ONSITE. ALL SUCH MATERIALS WILL BE DISPOSED OF IN PROPER WASTE DISPOSAL PROCEDURES.

POLLUTION CONTROL PROGRAM: WASTE MATERIAL SHALL NOT BE DISCHARGED TO WATERS OF THE STATE, EXCEPT AS AUTHORIZED BY A SECTION 404 PERMIT. THE STORM WATER DETENTION FACILITY AND PERMANENT BMPS SHALL HELP PREVENT ANY POLLUTANTS, THAT MAY HAVE DISCHARGED INTO THE STORM DRAINAGE SYSTEM, FROM ESCAPING THE SITE.

WASTE MATERIALS - ALL WASTE MATERIALS WILL BE COLLECTED AND STORED IN A SECURELY LIDDED METAL DUMPSTER. THE DUMPSTER WILL MEET ALL SOLID WASTE MANAGEMENT REGULATIONS. ALL TRASH AND CONSTRUCTION DEBRIS FROM THE SITE WILL BE DEPOSITED IN THE DUMPSTER. THE DUMPSTER WILL BE EMPTIED A MINIMUM OF ONCE PER WEEK OR MORE OFTEN IF NECESSARY AND TRASH WILL BE HAULED AS REQUIRED BY LOCAL REGULATIONS. NO CONSTRUCTION WASTE WILL BE BURIED ONSITE. ALL PERSONNEL WILL BE INSTRUCTED ON PROPER PROCEDURES FOR WASTE DISPOSAL. A NOTICE STATING THESE PRACTICES WILL BE POSTED AT THE JOBSITE AND THE CONTRACTOR WILL BE RESPONSIBLE FOR SEEING THAT THESE PROCEDURES ARE FOLLOWED.

YES 29. DESCRIPTION AND CHART OR TIMELINE OF THE INTENDED SEQUENCE OF MAJOR ACTIVITIES WHICH DISTURB SOILS FOR THE MAJOR PORTIONS OF THE SITE (I.E., INITIAL PERIMETER AND SEDIMENT STORAGE BMPS, CLEARING AND GRUBBING ACTIVITIES, EXCAVATION ACTIVITIES, UTILITY ACTIVITIES, TEMPORARY AND FINAL STABILIZATION).

TENTATIVE ACTIVITY SCHEDI II E

ACTIVITY	M	ONTH	01	1	HTMON	02	М	HTM	03	MC	HTM	04	N	IONTI	1 05	MONT	H 06
CONSTRUCTION EXIT																	
SEDIMENT BARRIER, TEMP SED BASIN																	
MAINTENANCE OF ES&PC BMPs																	
CLEARING AND GRUBBING, DEMO																	
GRADING																	
DUST CONTROL MULCHING																	
DISTURBED AREA STABILIZATION (WITH TEMPORARY SEEDING)																	
DISTURBED AREA STABILIZATION (WITH PERMANENT VEGETATION)																	
PAVING																	
CONSTRUCTION																	

11 YES 30. PROVIDE COMPLETE REQUIREMENTS OF INSPECTIONS AND RECORD KEEPING BY THE PRIMARY PERMITTEE.*

ISPECTIONS AND RECORD KEEPING: CONSTRUCTION ACTIVITIES WILL BE PERFORMED IN COMPLIANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL LAWS, RULES, AND REGULATIONS. CONSTRUCTION SITE MUST BE INSPECTED DAILY, WEEKLY, AND MONTHLY BY CERTIFIED PERSONNEL. RECORDS OF INSPECTIONS MUST BE KEPT IN ACCORDANCE WITH PART IV.D.4.A OF THIS PERMIT.

PRIMARY PERMITTEE REQUIREMENTS

- A. EACH DAY WHEN ANY TYPE OF CONSTRUCTION ACTIVITY HAS TAKE PLACE AT A PRIMARY PERMITTEE'S SITE, CERTIFIED PERSONNEL PROVIDED BY THE PRIMARY PERMITTEE SHALL INSPECT: (A) ALL AREAS AT THE PRIMARY PERMITTEE'S SITE WHERE PETROLEUM PRODUCTS ARE STORED, USED, OR HANDLED FOR SPILLS AND LEAKS FROM VEHICLES AND EQUIPMENT AND (B) ALL LOCATIONS AT THE PRIMARY PERMITTEE'S SITE WHERE VEHICLES ENTER OR EXIT THE SITE FOR EVIDENCE OF OFF-SITE SEDIMENT TRACKING. THESE INSPECTIONS MUST BE CONDUCTED UNTIL A NOTICE OF TERMINATION IS SUBMITTED.
- B. MEASURE AND RECORD RAINFALL WITHIN DISTURBED AREAS OF THE SITE THAT HAVE NOTE MET FINAL STABILIZATION ONCE EVERY 24 HOURS EXCEPT ANY NON-WORKING SATURDAY, NON-WORKING SUNDAY AND NON-WORKING FEDERAL HOLIDAY. THE DATA COLLECTED FOR THE PURPOSE OF COMPLIANCE WITH THIS PERMIT SHALL BE REPRESENTATIVE OF THE MONITORED ACTIVITY. MEASUREMENT OF RAINFALL MAY BE SUSPENDED IF ALL AREAS OF THE SITE HAVE UNDERGONE FINAL STABILIZATION OR ESTABLISHED A CROP OF ANNUAL VEGETATION AND A SEEDING OF TARGET PERENNIALS APPROPRIATE FOR THE REGION.
- C. CERTIFIED PERSONNEL (PROVIDED BY THE PRIMARY PERMITTEE) SHALL INSPECT THE FOLLOWING AT LEAST ONCE EVERY SEVEN (7) CALENDAR DAYS AND WITHIN 24 HOURS OF THE END OF A STORM THAT IS 0.5 INCHES RAINFALL OR GREATER (UNLESS SUCH STORM ENDS AFTER 5:00PM ON ANY FRIDAY OR ON ANY NON-WORKING SATURDAY, NON-WORKING SUNDAY OR ANY NON-WORKING FEDERAL HOLIDAY IN WHICH CASE THE INSPECTION SHALL BE COMPLETED BY THE END OF THE NEXT BUSINESS DAY AND/OR WORKING DAY, WHICHEVER OCCURS FIRST): (A) DISTURBED AREAS OF THE PRIMARY PERMITTEE'S CONSTRUCTION SITE; (B) AREAS USED BY THE PRIMARY PERMITTEE FOR STORAGE OF MATERIALS THAT ARE EXPOSED TO PRECIPITATION; AND (C) STRUCTURAL CONTROL MEASURES. EROSION AND SEDIMENT CONTROL MEASURES IDENTIFIED IN THE PLAN APPLICABLE TO THE PRIMARY PERMITTEE'S SITE SHALL BE OBSERVED TO ENSURE THAT THEY ARE OPERATING CORRECTLY. WHERE DISCHARGE LOCATIONS OR POINTS ARE ACCESSIBLE, THEY SHALL BE INSPECTED TO ASCERTAIN WHETHER EROSION CONTROL MEASURES ARE EFFECTIVE IN PREVENTING SIGNIFICANT IMPACTS TO RECEIVING WATER(S). FOR AREAS OF A SITE THAT HAVE UNDERGONE FINAL STABILIZATION OR ESTABLISHED A CROP OF ANNUAL VEGETATION AND A SEEDING OF TARGET PERENNIALS APPROPRIATE FOR THE REGION, THE PERMITTEE MUST COMPLY WITH PART IV.D.4.a(4). THESE INSPECTIONS MUST BE CONDUCTED UNTIL A NOTICE OF TERMINATION IS SUBMITTED.
- D. CERTIFIED PERSONNEL (PROVIDED BY THE PRIMARY PERMITTEE) SHALL INSPECT AT LEAST ONCE PER MONTH DURING THE TERM OF THIS PERMIT (I.E., UNTIL A NOTICE OF TERMINATION IS RECEIVED BY EPD) THE AREAS OF THE SITE THAT HAVE UNDERGONE FINAL STABILIZATION OR ESTABLISHED A CROP OF ANNUAL VEGETATION AND A SEEDING OF TARGET PERENNIALS APPROPRIATE FOR THE REGION. THESE AREAS SHALL BE INSPECTED FOR EVIDENCE OF, OR THE POTENTIAL FOR, POLLUTANTS ENTERING THE DRAINAGE SYSTEM AND THE RECEIVING WATER(S). EROSION AND SEDIMENT CONTROL MEASURES IDENTIFIED IN THE PLAN SHALL BE OBSERVED TO ENSURE THAT THEY ARE OPERATING CORRECTLY. WHERE DISCHARGE LOCATIONS OR POINTS ARE ACCESSIBLE, THEY SHALL BE INSPECTED TO ASCERTAIN WHETHER EROSION CONTROL MEASURES ARE EFFECTIVE IN PREVENTING SIGNIFICANT IMPACTS TO RECEIVING WATER(S).
- E. BASED ON THE RESULTS OF EACH INSPECTION, THE SITE DESCRIPTION AND THE POLLUTION PREVENTION AND CONTROL MEASURES IDENTIFIED IN THE EROSION, SEDIMENTATION AND POLLUTION CONTROL PLAN, THE PLAN SHALL BE REVISED AS APPROPRIATE NOT LATER THAN SEVEN (7) CALENDAR DAYS FOLLOWING EACH INSPECTION. IMPLEMENTATION OF SUCH CHANGES SHALL BE MADE AS SOON AS PRACTICAL BUT IN NO CASE LATER THAN SEVEN (7) CALENDAR DAYS FOLLOWING EACH INSPECTION. THE PRIMARY PERMITTEE MUST AMEND THE PLAN IN ACCORDANCE WITH THE GENERAL PERMIT PART IV.D.4.B.(5) WHEN A SECONDARY PERMITTEE NOTIFIES THE PRIMARY PERMITTEE OF ANY PLAN DEFICIENCIES.
- F. A REPORT OF EACH INSPECTION THAT INCLUDES THE NAME(S) OF CERTIFIED PERSONNEL MAKING EACH INSPECTION, THE DATE(S) OF EACH INSPECTION, CONSTRUCTION PHASE (I.E., INITIAL, INTERMEDIATE OR FINAL), MAJOR OBSERVATIONS RELATING TO THE IMPLEMENTATION OF THE EROSION, SEDIMENTATION AND POLLUTION CONTROL PLAN, AND ACTIONS TAKEN IN ACCORDANCE WITH PART IV.D.4.a (5). OF THE PERMIT SHALL BE MADE AND RETAINED AT THE SITE OR BE READILY AVAILABLE AT A DESIGNATED ALTERNATE LOCATION UNTIL THE ENTIRE SITE OR THAT PORTION OF A CONSTRUCTION PROJECT THAT HAS BEEN PHASED HAS UNDERGONE FINAL STABILIZATION AND A NOTICE OF TERMINATION IS SUBMITTED TO EPD. SUCH REPORTS SHALL BE READILY AVAILABLE BY END OF THE SECOND BUSINESS DAY AND/OR WORKING DAY AND SHALL IDENTIFY ALL INCIDENTS OF BEST MANAGEMENT PRACTICES THAT HAVE NOT BEEN PROPERLY INSTALLED AND/OR MAINTAINED AS DESCRIBED IN THE PLAN. WHERE THE REPORT DOES NOT IDENTIFY ANY INCIDENTS. THE INSPECTION REPORT SHALL CONTAIN A CERTIFICATION THAT THE BEST MANAGEMENT PRACTICES ARE IN COMPLIANCE WITH THE EROSION, SEDIMENTATION AND POLLUTION CONTROL PLAN. THE REPORT SHALL BE SIGNED IN ACCORDANCE WITH PART V.G.2. OF THIS PERMIT.



MM

PROJECT NO.: 20-0130 DRAWN BY: MRK DESIGNED BY: MRK SURVEYED BY: BREWER SURVEY DATE: 2018 CHECKED BY: ABM

SCALE: N/A JANUARY 202

DATE:

SHEET

THE PRIMARY PERMITTEE MUST SAMPLE IN ACCORDANCE WITH THE PLAN AT LEAST ONCE FOR EACH RAINFALL EVENT DESCRIBED BELOW. FOR A QUALIFYING EVENT, THE PERMITTEE SHALL SAMPLE AT THE BEGINNING OF ANY STORM WATER DISCHARGE TO A MONITORED RECEIVING WATER AND/OR FROM A MONITORED OUTFALL LOCATION WITHIN FORTY-FIVE (45) MINUTES OR AS SOON AS POSSIBLE. HOWEVER, WHERE MANUAL AND AUTOMATIC SAMPLING ARE IMPOSSIBLE (AS DEFINED IN THE GENERAL PERMIT), OR ARE BEYOND THE PERMITTEE'S CONTROL, THE PERMITTEE SHALL TAKE SAMPLES AS SOON AS POSSIBLE, BUT IN NO CASE MORE THAN TWELVE (12) HOURS AFTER THE BEGINNING OF THE STORM WATER DISCHARGE.

SAMPLING BY THE PERMITTEE SHALL OCCUR FOR THE FOLLOWING QUALIFYING EVENTS:

- FOR EACH AREA OF THE SITE THAT DISCHARGES TO A RECEIVING WATER OR FROM AN OUTFALL, THE FIRST RAIN EVENT THAT REACHES OR EXCEEDS 0.5 INCH WITH A STORM WATER DISCHARGE THAT OCCURS DURING NORMAL BUSINESS HOURS AS DEFINED IN THIS PERMIT AFTER ALL CLEARING AND GRUBBING OPERATIONS HAVE BEEN COMPLETED, BUT PRIOR TO COMPLETION OF MASS GRADING OPERATIONS, IN THE DRAINAGE AREA OF THE LOCATION SELECTED AS THE SAMPLING
- IN ADDITION TO (A) ABOVE, FOR EACH AREA OF THE SITE THAT DISCHARGES TO A RECEIVING WATER OR FROM AN OUTFALL THE FIRST RAIN EVENT THAT REACHES OR EXCEEDS 0.5 INCH WITH A STORMWATER DISCHARGE THAT OCCURS DURING NORMAL BUSINESS HOURS AS DEFINED IN THIS PERMIT EITHER 90 DAYS AFTER THE FIRST SAMPLING EVENT OR AFTER ALL MASS GRADING OPERATIONS HAVE BEEN COMPLETED, BUT PRIOR TO SUBMITTAL OF A NOT, IN THE DRAINAGE AREA OF THE LOCATION SELECTED AS THE SAMPLING LOCATION, WHICHEVER COMES FIRST;
- AT THE TIME OF SAMPLING PERFORMED PURSUANT TO (A) AND (B) ABOVE, IF BMPS IN ANY AREA OF THE SITE THAT DISCHARGES TO A RECEIVING WATER OR FROM AN OUTFALL ARE NOT PROPERLY DESIGNED, INSTALLED AND MAINTAINED, CORRECTIVE ACTION SHALL BE DEFINED AND IMPLEMENTED WITHIN TWO (2) BUSINESS DAYS, AND TURBIDITY SAMPLES SHALL BE TAKEN FROM DISCHARGES FROM THAT AREA OF THE SITE FOR EACH SUBSEQUENT RAIN EVENT THAT REACHES OR EXCEEDS 0.5 INCH DURING NORMAL BUSINESS HOURS* UNTIL THE SELECTED TURBIDITY STANDARD IS ATTAINED, OR UNTIL POST-STORM EVENT INSPECTIONS DETERMINE THAT BMPS ARE PROPERLY DESIGNED, INSTALLED AND MAINTAINED;.
- WHERE SAMPLING PURSUANT TO (A), (B) OR (C) ABOVE IS REQUIRED BUT NOT POSSIBLE (OR NOT REQUIRED BECAUSE THERE WAS NO DISCHARGE), THE PERMITTEE, IN ACCORDANCE WITH PART IV.D.4.A.(6), MUST INCLUDE A WRITTEN JUSTIFICATION IN THE INSPECTION REPORT OF WHY SAMPLING WAS NOT PERFORMED. PROVIDING THIS JUSTIFICATION DOES NOT RELIEVE THE PERMITTEE OF ANY SUBSEQUENT SAMPLING OBLIGATIONS UNDER (A), (B) OR (C) ABOVE; AND
- EXISTING CONSTRUCTION ACTIVITIES, I.E., THOSE THAT ARE OCCURRING ON ORBEFORE THE EFFECTIVE DATE OF THIS PERMIT THAT HAVE MET THE SAMPLING REQUIRED BY (A) ABOVE SHALL SAMPLE IN ACCORDANCE WITH (B). THOSE EXISTING CONSTRUCTION ACTIVITIES THAT HAVE MET THE SAMPLING REQUIRED BY (B) ABOVE SHALL NOT BE REQUIRED TO CONDUCT ADDITIONAL SAMPLING OTHER THAN AS REQUIRED BY (C) ABOVE.

*NOTE THAT THE PERMITTEE MAY CHOOSE TO MEET THE REQUIREMENTS OF (A) AND (B) ABOVE BY COLLECTING TURBIDITY SAMPLES FROM ANY RAIN EVENT THAT REACHES OR EXCEEDS 0.5 INCH AND ALLOWS FOR SAMPLING AT ANY TIME OF THE DAY OR WEEK.

THE APPLICABLE PERMITTEES ARE REQUIRED TO SUBMIT THE SAMPLING RESULTS TO THE EPD AT THE ADDRESS SHOWN IN PART II.C. BY THE FIFTEENTH DAY OF THE MONTH FOLLOWING THE REPORTING PERIOD. REPORTING PERIODS ARE MONTHS DURING WHICH SAMPLES ARE TAKEN IN ACCORDANCE WITH THIS PERMIT. SAMPLING RESULTS SHALL BE IN A CLEARLY LEGIBLE FORMAT. UPON WRITTEN NOTIFICATION, EPD MAY REQUIRE THE APPLICABLE PERMITTEE TO SUBMIT THE SAMPLING RESULTS ON A MORE FREQUENT BASIS. SAMPLING AND ANALYSIS OF ANY STORMWATER DISCHARGE(S) OR THE RECEIVING WATER(S) BEYOND THE MINIMUM FREQUENCY STATED IN THIS PERMIT MUST BE REPORTED IN A SIMILAR MANNER TO THE EPD. THE SAMPLING REPORTS MUST BE SIGNED IN ACCORDANCE WITH PART V.G.2. SAMPLING REPORTS MUST BE SUBMITTED TO EPD USING THE ELECTRONIC SUBMITTAL SERVICE PROVIDED BY EPD. SAMPLING REPORTS MUST BE SUBMITTED TO EPD UNTIL SUCH TIME AS A NOT IS SUBMITTED IN ACCORDANCE WITH PART VI.

- 2. ALL SAMPLING REPORTS SHALL INCLUDE THE FOLLOWING INFORMATION:
 - A. THE RAINFALL AMOUNT, DATE, EXACT PLACE AND TIME OF SAMPLING OR MEASUREMENTS;
 - THE NAME(S) OF THE CERTIFIED PERSONNEL WHO PERFORMED THE SAMPLING AND MEASUREMENTS;
 - THE DATE(S) ANALYSES WERE PERFORMED;
 - THE TIME(S) ANALYSES WERE INITIATED;
 - THE NAME(S) OF THE CERTIFIED PERSONNEL WHO PERFORMED THE ANALYSES; REFERENCES AND WRITTEN PROCEDURES, WHEN AVAILABLE, FOR THE ANALYTICAL TECHNIQUES OR METHODS USED;
 - THE RESULTS OF SUCH ANALYSES, INCLUDING THE BENCH SHEETS, INSTRUMENT READOUTS, COMPUTER DISKS OR TAPES, ETC., USED TO DETERMINE THESE RESULTS:
 - RESULTS WHICH EXCEED 1000 NTU SHALL BE REPORTED AS "EXCEEDS 1000 NTU";
 - AND CERTIFICATION STATEMENT THAT SAMPLING WAS CONDUCTED AS PER THE PLAN.
- 3. ALL WRITTEN CORRESPONDENCE REQUIRED BY THIS PERMIT SHALL BE SUBMITTED BY RETURN RECEIPT CERTIFIED MAIL (OR SIMILAR SERVICE) TO THE APPROPRIATE DISTRICT OFFICE OF THE EPD ACCORDING TO THE SCHEDULE IN APPENDIX A OF THIS PERMIT. THE PERMITTÉE SHALL RETAIN A COPY OF THE PROOF OF SUBMITTAL AT THE CONSTRUCTION SITE OR THE PROOF OF SUBMITTAL SHALL BE READILY AVAILABLE AT A DESIGNATED LOCATION FROM COMMENCEMENT OF CONSTRUCTION UNTIL SUCH TIME AS A NOT IS SUBMITTED IN ACCORDANCE WITH PART VI.

12 YES 32. PROVIDE COMPLETE DETAILS FOR RETENTION OF RECORDS AS PER PART IV.F OF THE PERMIT.

THE PRIMARY PERMITTEE SHALL RETAIN THE FOLLOWING RECORDS AT THE CONSTRUCTION SITE OR THE RECORDS SHALL BE READILY AVAILABLE AT A DESIGNATED ALTERNATE LOCATION FROM COMMENCEMENT OF CONSTRUCTION UNTIL SUCH TIME AS A NOT IS SUBMITTED IN ACCORDANCE WITH PART VI:

- A COPY OF ALL NOTICES OF INTENT SUBMITTED TO EPD;
- A COPY OF THE EROSION, SEDIMENTATION AND POLLUTION CONTROL PLAN REQUIRED BY THIS PERMIT THE DESIGN PROFESSIONAL'S REPORT OF THE RESULTS OF THE INSPECTION CONDUCTED IN ACCORDANCE WITH PART IV.A.5.
- A COPY OF ALL SAMPLING INFORMATION, RESULTS, AND REPORTS REQUIRED BY THIS PERMIT.
- A COPY OF ALL INSPECTION REPORTS GENERATED IN ACCORDANCE WITH PART IV. D.4.A. OF THIS PERMIT
- A COPY OF ALL VIOLATION SUMMARIES AND VIOLATION SUMMARY REPORTS GENERATED IN ACCORDANCE WITH PART III.D.2. OF
- DAILY RAINFALL INFORMATION COLLECTED IN ACCORDANCE WITH PART IV.D.4.A(2). OF THIS PERMIT

COPIES OF ALL NOTICES OF INTENT, NOTICES OF TERMINATION, INSPECTION REPORTS, SAMPLING REPORTS (INCLUDING ALL CALIBRATION) AND MAINTENANCE RECORDS AND ALL ORIGINAL STRIP CHART RECORDINGS FOR CONTINUOUS MONITORING INSTRUMENTATION) OR OTHER REPORTS REQUESTED BY THE EPD. EROSION, SEDIMENTATION AND POLLUTION CONTROL PLANS, RECORDS OF ALL DATA USED TO COMPLETE THE NOTICE OF INTENT TO BE COVERED BY THIS PERMIT AND ALL OTHER RECORDS REQUIRED BY THIS PERMIT SHALL BE RETAINED BY THE PERMITTEE WHO EITHER PRODUCED OR USED IT FOR A PERIOD OF AT LEAST THREE YEARS FROM THE DATE THAT THE NOT IS SUBMITTED IN ACCORDANCE WITH PART VI. OF THIS PERMIT. THESE RECORDS MUST BE MAINTAINED AT THE PERMITTEE'S PRIMARY PLACE OF BUSINESS OR AT A DESIGNATED ALTERNATIVE LOCATION ONCE THE CONSTRUCTION ACTIVITY HAS CEASED AT THE PERMITTED SITE. THIS PERIOD MAY BE EXTENDED BY REQUEST OF THE EPD AT ANY TIME UPON WRITTEN NOTIFICATION TO THE

12 YES 33. DESCRIPTION OF ANALYTICAL METHODS TO BE USED TO COLLECT AND ANALYZE THE SAMPLES FROM EACH LOCATION.

ALL SAMPLING TO BE PERFORMED IN ACCORDANCE WITH PART IV.D.6.b OF GAR100001.

SITE FLOW CHARACTERISTICS AND SAMPLING LOCATION STORM WATER RUNOFF SHALL SHEET FLOW ACROSS THE PROPERTY AND BE COLLECTED BY INLETS OR FLUMES. STORM WATER WILL

THEN BE CONVEYED VIA STORM DRAINAGE PIPING INTO PROPOSED BIORETENTION AREAS THAT OUTFALL INTO AN EXISTING DETENTION POND. THIS OUTFALL IS THE LOCATION AT WHICH ALL TURBIDITY SAMPLES SHALL BE TAKEN. STORM WATER COLLECTED IN THE DRAINAGE SYSTEM DISCHARGES INTO PIPE MAKERS CANAL, AND THEN INTO GUM BRANCH.

*NOTE THAT THE PERMITTEE MAY CHOOSE TO MEET THE REQUIREMENTS OF (A) AND (B) ABOVE BY COLLECTING TURBIDITY SAMPLES FROM ANY RAIN EVENT THAT REACHES OR EXCEEDS 0.5 INCH AND ALLOWS FOR SAMPLING AT ANY TIME OF THE DAY OR WEEK.

APPENDIX B RATIONALE FOR NTU VALUES AT ALL OUTFALL SAMPLING POINTS WHERE APPLICABLE.*

STORM WATER IS TO BE SAMPLED FOR NEPHELOMETRIC TURBIDITY UNITS (NTU) OF THE OUTFALL LOCATION. A DISCHARGE OF STORM WATER RUNOFF FROM DISTURBED AREAS WHERE BEST MANAGEMENT PRACTICES HAVE NOT BEEN PROPERLY DESIGNED, INSTALLED, AND MAINTAINED SHALL CONSTITUTE A SEPARATE VIOLATION FOR EACH DAY ON WHICH SUCH CONDITION RESULTS IN THE TURBIDITY OF THE DISCHARGE EXCEEDING 75, THE VALUE THAT WAS SELECTED FROM APPENDIX B IN GENERAL PERMIT. THE NTU IS BASED UPON THE DISTURBED ACREAGE OF 1.65 ACRES FOR THE PROJECT SITE, THE SURFACE WATER DRAINAGE AREA OF 0.10-SQUARE MILES FOR THE DRAINAGE BASIN, AND THE RECEIVING WATER UNNAMED TRIBUTARY TO FOREST RIVER, WHICH SUPPORTS WARM WATER FISHERIES.

DELINEATE ALL SAMPLING LOCATIONS ON ALL PHASES OF THE PLAN, PERENNIAL AND INTERMITTENT STREAMS AND OTHER WATER BODIES

A DESCRIPTION OF APPROPRIATE CONTROLS AND MEASURES THAT WILL BE IMPLEMENTED AT THE CONSTRUCTION SITE INCLUDING: (1) INITIAL SEDIMENT STORAGE REQUIREMENTS AND PERIMETER CONTROL BMPS, (2) INTERMEDIATE GRADING AND DRAINAGE BMPS, AND (3) FINAL BMPS. FOR CONSTRUCTION SITES WHERE THERE WILL BE NO MASS GRADING AND THE INITIAL PERIMETER CONTROL BMPS, INTERMEDIATE GRADING AND DRAINAGE BMPS, AND FINAL BMPS ARE THE SAME, THE PLAN MAY COMBINE ALL OF THE BMPS INTO A SINGLE

37. GRAPHIC SCALE AND NORTH ARROW.

38. EXISTING AND PROPOSED CONTOUR LINES WITH CONTOUR LINES DRAWN AT AN INTERVAL IN ACCORDANCE WITH THE FOLLOWING

Map Scale	Ground Slope	Contour Intervals, ft.
1 inch = 100ft or	Flat 0 - 2%	0.5 or 1
larger scale	Rolling 2 - 8%	1 or 2
	Steep 8% +	2,5 or 10

39. USE OF ALTERNATIVE BMPS WHOSE PERFORMANCE HAS BEEN DOCUMENTED TO BE EQUIVALENT TO OR SUPERIOR TO CONVENTIONAL BMPS AS CERTIFIED BY A DESIGN PROFESSIONAL (UNLESS DISAPPROVED BY EPD OR THE GEORGIA SOIL AND WATER CONSERVATION COMMISSION). PLEASE REFER TO THE ALTERNATIVE BMP GUIDANCE DOCUMENT FOUND AT WWW.GASWCC.ORG.

PLEASE REFER TO THE ALTERNATIVE BMP GUIDANCE DOCUMENT FOUND AT WWW.GASWCC.ORG.

40. USE OF ALTERNATIVE BMP FOR APPLICATION TO THE EQUIVALENT BMP LIST. PLEASE REFER TO APPENDIX A-2 OF THE MANUAL FOR EROSION & SEDIMENT CONTROL IN GEORGIA 2016* EDITION. PLEASE REFER TO THE ALTERNATIVE EQUIVALENT BMP LIST IN APPENDIX OF A-2 OF THE MANUAL FOR EROSION & SEDIMENT

CONTROL IN GEORGIA 2016 EDITION.* 41. DELINEATION OF THE APPLICABLE 25-FOOT OR 50-FOOT UNDISTURBED BUFFERS ADJACENT TO STATE WATERS AND ANY ADDITIONAL BUFFERS REQUIRED BY THE LOCAL ISSUING AUTHORITY. CLEARLY NOTE AND DELINEATE ALL AREAS OF IMPACT.

ALL STATE WATERS ON OR WITHIN 200 FEET FROM THE PROJECT SITE MUST BE DELINEATED ON ALL PHASES OF THE PLAN. ALL WETLANDS LOCATED WITHIN THE PROJECT SITE MUST BE DELINEATED.

42. DELINEATION OF ALL STATE WATERS AND WETLANDS LOCATED ON AND WITHIN 200 FEET OF THE PROJECT SITE. N/A NO HYDRO YES 43. DELINEATION AND ACREAGE OF CONTRIBUTING DRAINAGE BASINS ON THE PROJECT SITE.

- 44. PROVIDE HYDROLOGY STUDY AND MAPS OF DRAINAGE BASINS FOR BOTH PRE AND POST-DEVELOPMENT CONDITIONS. 45. AN ESTIMATE OF THE RUNOFF COEFFICIENT OR PEAK DISCHARGE FLOW OF THE SITE PRIOR TO AND AFTER CONSTRUCTION
- HYDRO YES HYDRO YES
 - 46. STORM DRAIN PIPE AND WEIR VELOCITIES WITH APPROPRIATE OUTLET PROTECTION TO ACCOMMODATE DISCHARGES WITHOUT EROSION. IDENTIFY/DELINEATE AT ALL STORM WATER DISCHARGE POINTS.
- 47. SOIL SERIES FOR THE PROJECT SITE AND THEIR DELINEATION. 10 YES

8-10 YES

11 YES

HYDRO YES

48. THE LIMITS OF DISTURBANCE FOR EACH PHASE OF CONSTRUCTION.

49. PROVIDE A MINIMUM OF 67 CUBIC YARDS OF SEDIMENT STORAGE PER ACRE DRAINED USING A TEMPORARY SEDIMENT BASIN. RETROFITTED DETENTION POND, AND/OR EXCAVATED INLET SEDIMENT TRAPS FOR EACH COMMON DRAINAGE LOCATION. SEDIMENT STORAGE VOLUME MUST BE IN PLACE PRIOR TO AND DURING ALL LAND DISTURBANCE ACTIVITIES UNTIL FINAL STABILIZATION OF THE SITE HAS BEEN ACHIEVED. A WRITTEN JUSTIFICATION EXPLAINING THE DECISION TO USE EQUIVALENT CONTROLS WHEN A SEDIMENT BASIN IS NOT ATTAINABLE MUST BE INCLUDED IN THE PLAN FOR EACH COMMON DRAINAGE LOCATION IN WHICH A SEDIMENT BASIN IS NOT PROVIDED. A WRITTEN JUSTIFICATION AS TO WHY 67 CUBIC YARDS OF STORAGE IS NOT ATTAINABLE MUST ALSO BE GIVEN. WORKSHEETS FROM THE MANUAL MUST BE INCLUDED FOR STRUCTURAL BMPS AND ALL CALCULATIONS USED BY THE DESIGN PROFESSIONAL TO OBTAIN THE REQUIRED SEDIMENT STORAGE WHEN USING EQUIVALENT CONTROLS. WHEN DISCHARGING FROM SEDIMENT BASINS AND IMPOUNDMENTS, PERMITTEES ARE REQUIRED TO UTILIZE OUTLET STRUCTURES THAT WITHDRAW WATER FROM THE SURFACE, UNLESS INFEASIBLE. IF OUTLET STRUCTURES THAT WITHDRAW WATER FROM THE SURFACE ARE NOT FEASIBLE, A WRITTEN JUSTIFICATION EXPLAINING THIS DECISION MUST BE INCLUDED IN THE PLAN.

SEDIMENT STORAGE:

INITAL SEDIMENT STORAGE:

BASIN IS 0.08-ACRES. THE REQUIRED SEDIMENT STORAGE VOLUME FOR THIS ACREAGE IS 67 CY/AC * 0.08-ACRES = 5.36 CY. THE SEDIMENT WILL BE TRAPPED BY THE SILT FENCE SINCE THE INSTALLATION OF THE SILT FENCE IS ALL THAT WILL BE DISTURBED IN THE INITIAL PHASE.

INLET SEDIMENT TRAP CALCULATIONS

EXCAVATED INLET SEDIMENT STORAGE CALCULATION FOR EACH PROPOSED INLET:

- 1. TOTAL DRAINAGE AREA = 1.54 AC NUMBER OF INLETS = $\underline{2}$
- REQUIRED SEDIMENT STORAGE = 67 CY/AC * DRAINAGE AREA REQUIRED SEDIMENT STORAGE = 67 CY/AC * 1.54 AC REQUIRED SEDIMENT STORAGE = $\underline{103}$ CY = $\underline{2,781}$ CF SEDIMENT STORAGE PER INLET = 1,390 CF
- 3. EXCAVATION DEPTH (MINIMUM OF 1.5 FT.) = $\underline{2.0}$ FT
- 4. SLOPE OF SIDES (SHALL NOT BE STEEPER THAN 2:1) = 2:1
- 5. REQUIRED SURFACE AREA/EXCAVATED SEDIMENT TRAP SAmin = REQUIRED SEDIMENT STORAGE/ SEDIMENT DEPTH SAmin = 1,390 CF/ 2.0 FT SAmin = $\overline{695}$ SF min
- SHAPE OF EXCAVATION AND DETERMINE DIMENSIONS. (A RECTANGULAR SHAPE WITH 2:1 LENGTH TO WIDTH RATIO IS RECOMMENDED.)
- DIMENSIONS: L = $\underline{27}$ FT W = $\underline{27}$ FT DIAMETER (IF APPLICABLE) = $\underline{N/A}$ FT
- 7. TOTAL SEDIMENT STORED BY SEDIMENT TRAPS = 2,918-CF = 108-CY

50. LOCATION OF BEST MANAGEMENT PRACTICES THAT ARE CONSISTENT WITH, AND NO LESS STRINGENT THAN, THE MANUAL FOR EROSION AND SEDIMENT CONTROL IN GEORGIA. USE UNIFORM CODING SYMBOLS FROM THE MANUAL, CHAPTER 6, WITH LEGEND.

GEORGIA UNIFORM CODING SYSTEM ESPC STRUCTURAL PRACTICES

CODE	PRACTICE	DETAIL	MAP SYMBOL	DESCRIPTION
Co	CONSTRUCTION EXIT		Co (LABEL)	A CRUSHED STONE PAD LOCATED AT THE CONSTRUCTION SITE EXIT TO PROVIDE A PLACE FOR REMOVING MUD FROM TIRES THEREBY PROTECTING PUBLIC STREETS.
Sd1	SEDIMENT BARRIER		(INDICATE TYPE)	A BARRIER TO PREVENT SEDIMENT FROM LEAVING THE CONSTRUCTION SITE. IT MAY BE SANDBAGS, BALES OF STRAW OR HAY, BRUSH, LOGS AND POLES, OR A SILT FENCE.
Sd2	INLET SEDIMENT TRAP	*		A TEMPORARY PROTECTIVE DEVICE FORMED AT OR AROUND AN INLET TO A STORM DRAIN TO TRAP SEDIMENT.
St	STORMDRAIN OUTLET PROTECTION		St	A PAVED OR SHORT SECTION OF RIPRAP CHANNEL AT THE OUTLET OF A STORM DRAIN SYSTEM PREVENTING EROSION FROM THE CONCENTRATED RUNOFF.

GEORGIA UNIFORM CODING SYSTEM **ESPC VEGETATIVE PRACTICES**

C	ODE	PRACTICE	DETAIL	MAP SYMBOL	DESCRIPTION
)s1	DISTURBED AREA STABILIZATION (WITH MULCHING ONLY)		Ds1	ESTABLISHING TEMPORARY PROTECTION FOR DISTURBED AREAS WHERE SEEDLINGS MAY NOT HAVE A SUITABLE GROWING SEASON TO PRODUCE AN EROSION RETARDING COVER.
	s2	DISTURBED AREA STABILIZATION (WITH TEMP SEEDING)		Ds2	ESTABLISHING A TEMPORARY VEGETATIVE COVER WITH FAST GROWING SEEDINGS ON DISTURBED AREAS.
)s3	DISTURBED AREA STABILIZATION (WITH PERM SEEDING)	W. W. G. W.	Ds3	ESTABLISHING A PERMANENT VEGETATIVE COVER SUCH AS TREES, SHRUBS, VINES, GRASSES, OR LEGUMES ON DISTURBED AREAS.
	Du	DUST CONTROL ON DISTURBED AREAS		Du	CONTROLLING SURFACE AND AIR MOVEMENT OF DUST ON CONSTRUCTION SITE, ROADWAYS AND SIMILAR SITES.
	Ss	SLOPE STABILIZATION		Ss	A PROTECTIVE COVERING USED TO PREVENT EROSION AND ESTABLISH TEMPORARY OR PERMANENT VEGETATION ON STEEP SLOPES, SHORE LINES, OR CHANNELS.

PROVIDE DETAILED DRAWINGS FOR ALL STRUCTURAL PRACTICES. SPECIFICATIONS MUST, AT A MINIMUM, MEET THE GUIDELINES SET FORTH IN THE MANUAL FOR EROSION AND SEDIMENT CONTROL IN GEORGIA.

PROVIDE VEGETATIVE PLAN. NOTING ALL TEMPORARY AND PERMANENT VEGETATIVE PRACTICES. INCLUDE SPECIES, PLANTING DATES AND SEEDING, FERTILIZER, LIME AND MULCHING RATES. VEGETATIVE PLAN SHALL BE SITE SPECIFIC FOR APPROPRIATE TIME OF YEAR THAT SEEDING WILL TAKE PLACE AND FOR THE APPROPRIATE GEOGRAPHIC REGION OF GEORGIA.

TEMPORARY AND PERMANENT SEEDING SCHEDULE

	T	RATE PE		ORARY & PERMANE	RATE PE	
MONTH	TEMPORARY COVER	SEEDED ALONE	ADDED TO MIX	PERMANENT COVER	SEEDED ALONE	ADDED TO MIX
JANUARY	RYEGRASS	40 LBS	_	UNHULLED BERMUDA	10 LBS	6 LBS
	RYE	3 BU	0.5 BU	SERLCEA LESPEDEZA (1)	75 LBS	_
FEBRUARY	ANNUAL LESPEDEZA	40 LBS	10 LBS	UNHULLED BERMUDA	10 LBS	6 LBS
	RYEGRASS	40 LBS	_	SERLCEA LESPEDEZA (1)	75 LBS	_
	RYE	3 BU	0.5 BU			
MARCH	WEEPING LOVEGRASS	4 LBS	2 LBS	PENSACOLA BAHIA	60 LBS	30 LB
	ANNUAL LESPEDEZA	40 LBS	10 LBS	HULLED BERMUDA	10 LBS	6 LBS
				SERLCEA LESPEDEZA (2)	60 LBS	1
APRIL	WEEPING LOVEGRASS	4 LBS	2 LBS	PENSACOLA BAHIA	60 LBS	30 LB
	SUDON GRASS	60 LBS	_	WEEPING LOVEGRASS	4 LBS	2 LBS
	BROWN TOP MILLET	40 LBS	10 LBS	HULLED BERMUDA	10 LBS	6 LBS
MAY	WEEPING LOVEGRASS	4 LBS	2 LBS	PENSACOLA BAHIA	60 LBS	30 LE
	SUDON GRASS	60 LBS	_	WEEPING LOVEGRASS	4 LBS	2 LBS
	BROWN TOP MILLET	40 LBS	10 LBS	HULLED BERMUDA	10 LBS	6 LBS
	PEARL MILLET	50 LBS	_	SERLCEA LESPEDEZA (2)	60 LBS	_
JUNE	PEARL MILLET	50 LBS	_	PENSACOLA BAHIA	60 LBS	30 LE
	SUDON GRASS	60 LBS	_	HULLED BERMUDA	10 LBS	6 LBS
	BROWN TOP MILLET	40 LBS	10 LBS			
JULY	PEARL MILLET	50 LBS	_	PENSACOLA BAHIA	60 LBS	30 LE
	SUDON GRASS	60 LBS	_			
	BROWN TOP MILLET	40 LBS	10 LBS			
AUGUST	PEARL MILLET	50 LBS	_	PENSACOLA BAHIA	60 LBS	30 LE
	RYE	3 BU	0.5 BU			
SEPTEMBER	RYEGRASS	40 LBS	_	SERLCEA LESPEDEZA (1)	75 LBS	_
<u> </u>	OATS	4 BU	1 BU		, , , , , , ,	
	WHEAT	3 BU	0.5 BU			
OCTOBER	WHEAT	3 BU	0.5 BU	SERLCEA LESPEDEZA (1)	75 LBS	_
	RYEGRASS	40 LBS	_			
	RYE	3 BU	0.5 BU			
	BARLEY	3 BU	0.5 BU			
	OATS	4 BU	1 BU			
NOVEMBER	SAME AS OCTOBER			UNHULLED BERMUDA	10 LBS	6 LBS
DECEMBER	SAME AS OCTOBER			UNHULLED BERMUDA	10 LBS	6 LBS

1. UNSCARIFIED

2. SCARIFIED

RIPRAP APRON

3. CENTIPEDE SOD CAN BE USED AS PERMANENT COVER ANYTIME EXCEPT JUNE THRU OCTOBER. 4. LISTED IN THE ORDER OF PREFERENCE.


5. ALL PERMANENT GRASS PLANTINGS SHALL BE MULCHED.


FERTILIZING - APPLY 6-12-12 FERTILIZER AT THE RATE OF 35 POUNDS PER 1,000 SQUARE FEET, RAKING LIGHTLY INTO THE SOIL APPLY AGRICULTURAL LIME AT A RATE OF ONE TON PER ACRE. THE AGRICULTURAL LIME SHALL MEET THE SPECIFICATIONS OF THE GEORGIA DEPARTMENT OF AGRICULTURE.


- DRY STAW SHALL BE APPLIED AT THE RATE OF 2 TONS PER ACRE AND DRY HAY SHALL BE APPLIED
- AT A RATE OF 2.5 TONS PER ACRE. WATER IMMEDIATLEY AFTER MULCHING.

PIPE OUTLET TO FLAT AREA --NO WELL DEFINED CHANNEL

PIPE OUTLET TO WELL DEFINED CHANNEL







1. La IS THE LENGTH OF THE RIPRAP

- 2. D = 1.5 TIMES THE MAXIMUM STONE DIAMETER BUT NOT LESSHAN 6".
- 3. IN A WELL-DEFINED CHANNEL, EXTEND THE APRON UP THE CHANNEL BANKS TO AN ELEVATION OF 6" ABOVE THE MAXIMUM TAILWATER DEPTH OR TO THE TOP OF THE BANK (WHICHEVER IS LESS)

4. A FILTER BLANKET OR FILTER FABRIC

SHOULD BE INSTALLED BETWEEN THE RIPRAP AND THE SOIL FOUNDATION.

	Fl	OW CHARAC	TERISTICS		OUTLET	PROTECT	ION DIME	NSIONS
	PIPE	FLOW RATE (CFS)	VELOCITY (FPS)	TAILWATER CONDITION	La (FT)	W1 (FT)	W2 (FT)	d50
St-1	(3) 36" RCP	39.57	5.60	< 0.5 x (PIPE DIA.)	13	9	16	MIN. OF 6"
St-2	3' WIDE FLUME	32.60	21.74	< 0.5 x (PIPE DIA.)	8	9	11	MIN. OF 6"
St-3	3' WIDE FLUME	41.98	27.99	< 0.5 x (PIPE DIA.)	14	9	17	MIN. OF 6"
St-4	3' WIDE FLUME	52.89	35.26	< 0.5 x (PIPE DIA.)	18	9	21	MIN. OF 6"
St-5	3' WIDE FLUME	52.89	35.26	< 0.5 x (PIPE DIA.)	18	9	21	MIN. OF 6"
St-6	3' WIDE FLUME	52.89	35.26	< 0.5 x (PIPE DIA.)	18	9	21	MIN. OF 6"
St-7	3' WIDE FLUME	52.89	35.26	< 0.5 x (PIPE DIA.)	18	9	21	MIN. OF 6"


RIPRAP OUTLET PROTECTION NOT TO SCALE

St

5 | 6 | 6 | 6

Alec B Metzger

Level II Certified Design Professional Certification Number: 0000008757




DRAWN BY: MRK DESIGNED BY: MRK SURVEYED BY: BREWER SURVEY DATE: 2018 CHECKED BY: ABM SCALE: N/A

DATE: JANUARY 202 SHEET


- 1. AVOID LOCATING ON STEEP SLOPES OR AT CURVES ON PUBLIC ROADS. 2. REMOVE ALL VEGETATION AND OTHER UNSUITABLE MATERIAL FROM THE FOUNDATION AREA, GRADE, AND
- 3. AGGREGATE SIZE SHALL BE IN ACCORDANCE WITH NATIONAL STONE ASSOCIATION R-2 (1.5"-3.5" STONE). 4. GRAVEL PAD SHALL HAVE A MINIMUM THICKNESS OF 6".
- 5. PAD WIDTH SHALL BE EQUAL FULL WIDTH AT ALL POINTS OF VEHICULAR EGRESS, BUT NO LESS THAN 20'. $6.\;$ A DIVERSION RIDGE SHOULD BE CONSTRUCTED WHEN GRADE TOWARD PAVED AREA IS GREATER THAN 2%..
- 7. INSTALL PIPE UNDER THE ENTRANCE IF NEEDED TO MAINTAIN DRAINAGE DITCHES.
- 8. WHEN WASHING IS REQUIRED, IT SHOULD BE DONE ON AN AREA STABILIZED WITH CRUSHED STONE THAT DRAINS INTO AN APPROVED SEDIMENT TRAP OR SEDIMENT BASIN (DIVERT ALL SURFACE RUNOFF AND DRAINAGE FROM THE ENTRANCE TO A SEDIMENT CONTROL DEVICE).
- WASHRACKS AND/OR TIRE WASHERS MAY BE REQUIRED DEPENDING ON SCALE AND CIRCUMSTANCE. IF NECESSARY, WASHRACK DESIGN MAY CONSIST OF ANY MATERIAL SUITABLE FOR TRUCK TRAFFIC THAT REMOVE MUD AND DIRT.
- 10. MAINTAIN AREA IN A WAY THAT PREVENTS TRACKING AND/OR FLOW OF MUD ONTO PUBLIC RIGHTS-OF-WAYS. THIS MAY REQUIRE TOP DRESSING, REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT.


CRUSHED STONE CONSTRUCTION EXIT





SECTION A-A






1. BALES SHOULD BE BOUND WITH WIRE OR NYLON STRING AND SHOULD BE PLACED IN ROWS WITH BALE ENDS TIGHTLY ABUTTING THE ADJACENT BALES.

- 2. REMOVE #4 REBAR AFTER STRAW BALES ARE NO LONGER IN PLACE.
- 3. POINT C OF SECTION B-B SHOULD ALWAYS BE HIGHER THAN POINT D.

TYPICAL STRAW BALE CHECKDAM

NOT TO SCALE






NOTES:

1. USE STEEL OR WOOD POSTS OR AS SPECIFIED BY THE EROSION, SEDIMENTATION, AND POLLUTION CONTROL PLAN.

2. HEIGHT (*) IS TO BE SHOWN ON THE EROSION, SEDIMENTATION, AND POLLUTION

SILT FENCE - TYPE NON-SENSITIVE (Sd1-NS)





	CHEMICA	L CONTRO	L
ADHESIVE	WATER DILUTION	TYPE OF NOZZLE	APPLICATION RATE (GAL/AC)
ANIOIC ASPHALT EMULSION	7.1*	SPRAY	1200
LATEX EMULSION	12 1/2:1*	FINE SPRAY	235
RESIN-IN- WATER EMULSION	4: 1*	FINE SPRAY	300

*USE MANUFACTURER'S RECOMMENDATIONS WHEN AVAILABLE

- TEMPORARY METHODS
- PERMANENT METHODS MULCHES - TEMPORARY VEGETATIVE COVER
- SPRAY ON ADHESIVES
- TELLAGE IRRIGATION
- BARRIERS - CALCIUM CHLORIDE

DUST CONTROL NOT TO SCALE



TOPSOILING

STONE COVER

PERMANENT VEGETATION

DISTURBED AREA STABILIZATION (WITH PERMANENT SEEDING)

INSTALLATION:

- USE CONVENTIONAL PLANTING METHODS WHERE POSSIBLE
- FINAL STABILIZATION MEANS THAT 100% OF THE SOIL SURFACE IS UNIFORMLY COVERED IN PERMANENT VEGETATION WITH A DENSITY OF 70% OR GREATER, OR LANDSCAPED ACCORDING
- TO THE PLAN, OR EQUIVALENT PERMANENT STABILIZATION MEASURES. SELECT PLANT SPECIES BASED ON SITE AND SOIL CONDITIONS, PLANNED USE, AND MAINTENANCE OF THE AREA, TIME OF YEAR, METHOD OF PLANTING, AND THE NEEDS OF THE
- APPLY AGRICULTURAL LIME AT A RATE OF 1-2 TONS/ACRE UNLESS SOIL TESTS INDICATE OTHERWISE. PLEASE REFER TO TABLE 2 FOR INITIAL FERTILIZATION, NITROGEN, TOPDRESSING,
- AND MAINTENANCE FERTILIZER REQUIREMENTS FOR EACH SPECIES. APPLY SEED HYDRAULICALLY. IF USING CONVENTIONAL METHODS, USE A CULTI-PACKER
- SEEDER, DRILL, ROTARY SEEDER, OR BY HAND. • COVER THE SEED LIGHTLY WITH $\frac{1}{8}$ " - $\frac{1}{4}$ " OF SOIL FOR SMALL SEED AND $\frac{1}{2}$ " - 1" OF SOIL FOR LARGE
- SEED WHEN USING A CULTIPACKER. CHECK SEED TAGS FOR % GERMINATION & % PURITY IN ORDER TO CALCULATE PURE LIVE SEED.
- (PLS), WHICH IS THE PERCENTAGE OF THE SEEDS THAT ARE PURE AND WILL GERMINATE. MULCH IS REQUIRED FOR ALL PERMANENT VEGETATION APPLICATIONS.
- IRRIGATE WHEN THE SOIL IS DRY AND A RATE THAT WILL NOT CAUSE RUNOFF.

- RE-SEED AREAS WHERE AN ADEQUATE STAND OF TEMPORARY VEGETATION FAILS TO EMERGE OR WHERE A POOR STAND EXISTS.
- MAINTAIN AT LEAST 6" OF TOP GROWTH UNDER ANY USE AND MANAGEMENT
- EXCLUDE TRAFFIC UNTIL THE PLANTS ARE WELL ESTABLISHED.
- PLEASE REFER TO TABLE 2 FOR SECOND YEAR AND MAINTENANCE FERTILIZER RATES.
- APPLY ONE TON OF AGRICULTRUAL LIME EVERY 4-6 YEARS OR AS INDICATED BY SOIL TESTS. MOW BERMUDAGRASS, BAHIAGRASS, AND TALL FESCUE AS DESIRED

PLANTING DAYS BY REGION


• MOW SERICEA LESPEDEZA ONLY AFTER FROST TO ENSURE THAT THE SEEDS ARE MATURE.

ARIE 1 SOME	TEMPORARY DI	ANT SPECIES	SEEDING BATES	AND PLANTING DATES
ADLL 1. SOIVIL		ANTO LOILO,	OLLDING IVAILO,	AND I LANTING DATES

SPECIES	RATE PER 1,000 SQ.	TEATE DED ACDE	PLANTIN	G DAYS B	REGION
Si LOILS	NATE LEN 1,000 SQ.	INAIL I LIC AOILL	M - L	Р	С
BAHIA, PENSACOLA ALONE OR W/ TEMP. COVER W/ OTHER PERENNIALS	1.4 LBS 0.7 LBS	60 LBS. 30 LBS.		4/1-5/31	3/1-5/31
BAHIA, WILMINGTON ALONE OR W/ TEMP. COVER W/ OTHER PERENNIALS	1.4 LBS 0.7 LBS	30 LBS 30 LBS	3/15-5/31	3/1-5/31	
BERMUDA, COMMON (HULLED SEED) ALONE W/ OTHER PERENNIALS	0.2 LBS 0.1 LBS	10.0 LBS 6.0 LBS		4/1-5/31	3/15-5/31
BERMUDA, COMMON (UNHULLED SEED) W/ TEMP. COVER W/ OTHER PERENNIALS	0.2 LBS 0.1 LBS	10.0 LBS 6.0 LBS		10/1-2/28	11/1-1/31
BERMUDA SPRINGS	0.9 CU. FT.	40 CU. FT.			
COMMON LAWN & FORAGE HYBRIDS	SOD PLUG	S 3' X 3'	4/15-6/15	4/1-6/15	4/1-5/31
CENTIPEDE	BLOCK SOD ONLY	BLOCK SOD ONLY		11/1-5/31	11/1-5/31
CROWN VETCH W/ WINTER ANNUALS OR COOL SEASON GRASSES	0.3 LBS	15 LBS	9/1-10/15	9/1-10/15	
FESCUE, TALL ALONE W/ OTHER PERENNIALS	1.1 LBS 0.7 LBS	50 LBS 30 LBS	3/1-4/15 OR 8/15-10/15	9/1-10/15	
LESPEDEZA, SERICEA					
SCARIFIED	1.4 LBS	60 LBS	4/1-5/31	3/15-5/31	3/1-5/15
UNSCARIFIED	1.7 LBS	75 LBS	9/1-2/28	9/1-2/28	9/1-2/28
SEED-BEARING HAY	138 LBS	3 TONS	10/1-2/28	10/1-1/31	10/15-1/15
LESPEDEZA AMBRO VIRGATA OR APPALOW					
SCARIFIED	1.4 LBS	60 LBS	4/1-5/31	3/15-5/31	3/1-5/15
UNSCARIFIED	1.7 LBS	75 LBS	9/1-2/28	9/1-2/28	9/1-2/28
LESPEDEZA, SHRUB (LESPEDEZA BICOLOR OR LESPEDEZA THUMBERGII) PLANTS	3' X 3' SPA	CING	10/1-3/31	11/1-3/15	11/15-2/28
LOVEGRASS, WEEPING ALONE W/ OTHER PERENNIALS	0.1 LBS 0.05 LBS	4 LBS 2 LBS	4/1-5/31	3/15-5/31	3/1-5/31
MAIDENCANE SPRIGS	2' X 3' SF	PACING	2/1-3/31	2/1-3/31	2/1-3/31
PANICGRASS, ATLANTIC COASTAL	0.5 LBS	20 LBS		3/1-4/30	3/1-4/30
RED CANARY GRASS W/ OTHER PERENNIALS	1.1 LBS 0.7 LBS	50 LBS 30 LBS	8/15-10/15	9/1-10/15	
SUNFLOWER, AZTEC MAXIMILLIAN	0.2 LBS	10 LBS	4/15-5/31	4/15-5/31	4/1-5/31

TABLE 2: FERTILIZER REQUIREMENTS FOR PERMANENT VEGETATION.

TABLE Z. FERTILIZER RE	EQUINCIVICITIES FO	ONFERMAN	ENI VEGET	ATION
TYPES OF SPECIES	PLANTING YEAR	FERTILIZER (N-P-K)	RATE (LBS/ACRE)	N TOP DRESSING RATE (LBS/ACRE)
COOL SEASON GRASSES	FIRST SECOND MAINTENANCE	6-12-12 6-12-12 10-10-10	1500 1000 400	50-100 30
COOL SEASON GRASSES & LEGUMES	FIRST SECOND MAINTENANCE	6-12-12 0-10-10 0-10-10	1500 1000 400	0-50
WARM SEASON GRASSES	FIRST SECOND MAINTENANCE	6-12-12 6-12-12 10-10-10	1500 800 400	50-100 50-100 30
WARM SEASON GRASSES & LEGUMES	FIRST SECOND MAINTENANCE	6-12-12 0-10-10 0-10-10	1500 1000 400	50



CONCRETE DUMPSTER PAD DETAIL NOT TO SCALE

Ds1 DISTURBED AREA STABILIZATION (MULCHING ONLY)

INSTALLATION:

- APPLY MULCH OR TEMPORARY GRASSING TO ALL EXPOSED AREAS WITHIN 14 DAYS OF
- APPLICABLE TO GRADED OR CLEARED AREAS WHERE SEEDINGS MAY NOT HAVE A SUITABLE GROWING SEASON TO PRODUCE AN EROSION RETARDANT COVER.
- MULCH CAN BE USED AS A SINGULAR EROSION CONTROL DEVICE FOR UP TO 6 MONTHS. • APPLY AT THE APPROPRIATE DEPTH. REFER TO TABLE 1 FOR SPECIFIC MATERIALS.

TABLE 1: MULCHING APPLICATION REQUIREMENTS

MATERIAL	RATE	DEPTH
STRAW OR HAY	2 - 2.5 TONS/ACRE	2" TO 4"
WOOD WASTE, CHIPS, SAWDUST, BARK	-	2" TO 3"
POLYETHYLENE FILM	SECURE WITH SOIL, ANCHORS, WEIGHTS	-
GEOTEXTILES, JUTE MATTING, NETTING, ETC.	SEE MANUFACTURER'S RECOMMENDATIONS	

SITE PREPARATION:

- GRADE TO PERMIT THE USE OF EQUIPMENT FOR APPLYING AND ANCHORING MULCH.
- INSTALL NEEDED EROSION CONTROL MEASURES SUCH AS DIKES, BERMS, AND SEDIMENT
- LOOSEN COMPACTED SOIL TO A MINIMUM DEPTH OF 3".

APPLYING MULCH:

- APPLY DRY STRAW OR HAY AND WOOD CHIPS UNIFORMLY BY HAND OR BY MECHANICAL
- APPLY 20-30 LBS OF NITROGEN / ACRE IF THE AREA WILL EVENTUALLY BE COVERED WITH PERENNIAL VEGETATION.
- APPLY POLYETHYLENE FILM ON EXPOSED AREAS.

ANCHORING MULCH:

- PRESS STRAW OR HAY INTO THE SOIL WITH A DISK HARROW IMMEDIATELY AFTER APPLICATION. TACKIFIERS MAY BE USED WHEN SPREADING MULCH WITH BLOWER-TYPE EQUIPMENT.
- ANCHOR WOOD WASTE USING THE APPROPRIATE SIZE NETTING. TRENCH POLYETHYLENE AT THE TOP AS WELL AS INCREMENTALLY AS NECESSARY.

MAINTENANCE:

THE APPROPRIATE DEPTH AND 90% COVER SHALL BE MAINTAINED AT ALL TIMES.

DISTURBED AREA STABILIZATION (WITH TEMPORARY SEEDING)

INSTALLATION:

- APPLY MULCH OR TEMPORARY GRASSING TO ALL EXPOSED AREAS WITHIN 14 DAYS OF
- APPLICABLE TO ROUGH GRADED AREAS THAT WILL BE EXPOSED FOR LESS THAN 6 MONTHS. COORDINATE WITH PERMANENT MEASURES TO ENSURE ECONOMICAL AND EFFECTIVE
- TAKE NOTE OF WHICH SPECIES ARE NOT APPROPRIATE FOR COMPANION CROP PLANTINGS. WHEN THE SOIL HAS BEEN SEALED BY RAINFALL OR CONSISTS OF SMOOTH CUT SLOPES,
- SCARIFY THE SOIL IN ORDER TO PROVIDE A PLACE FOR THE SEED TO LODGE AND GERMINATE. APPLY AGRICULTURAL LIME A THE RATE DETERMINED BY SOIL TEST PH. (TYP. 1 TON/ACRE)
- APPLY LIME BEFORE LAND PREPARATION AND INCORPORATE WITH A DISK, RIPPER, OR CHISEL ON STEEP SLOPES, APPLY FERTILIZER HYDRAULICALLY.
- SELECT GRASS OR GRASS-LEGUME MIXTURES BASED ON THE AREA AND SEASON OF THE YEAR. • APPLY SEED UNIFORMLY BY HAND, CYCLONE SEEDER, DRILL, CULTI-PACKER-SEEDER, OR HYDRAULIC SEEDER.
- THE APPROPRIATE DEPTH OF PLANTING IS 10x THE SEED DIAMETER. APPLY IRRIGATION AT A RATE THAT WILL NOT CAUSE RUNOFF AND EROSION. THOROUGHLY WET THE SOIL TO INSURE GERMINATION OF THE SEED.

MAINTENANCE:

 RE-SEED AREAS WHERE AN ADEQUATE STAND OF TEMPORARY VEGETATION FAILS TO EMERGE. IF OPTIMUM CONDITIONS FOR TEMPORARY VEGETATION IS LACKING, MULCH CAN BE USED AS A SINGULAR EROSION CONTROL DEVICE.

TABLE 1. SOME TEMPORARY PLANT SPECIES, SEEDING RATES, AND PLANTING DATES

SPECIES	RATE PER 1,000 SQ.	ETRATE DED ACDE	PLANTIN	G DAYS B	Y REGION
JF EGILS	KAIL FER 1,000 3Q.	TIMATE PER AGRE	M - L	Р	С
BARLEY ALONE BARLEY IN MIXTURES	3.3 LBS 0.6 LBS	3.0 BU 0.5 BU	9/1-10/31	9/15-11/15	10/1-12/31
LESPEDEZA, ANNUAL LESPEDEZA IN MIXTURES	0.9 LBS 0.2 LBS	40 LBS 10 LBS	3/1-3/31	3/1-3/31	2/1-2/28
LOVEGRASS, WEEPING LOVEGRASS IN MIXTURES	0.1 LBS 0.05 LBS	4.0 LBS 2.0 LBS	4/1-5/31	4/1-5/31	3/1-5/31
MILLET, BROWNTOP MILLET IN MIXTURES	0.9 LBS 0.2 LBS	40 LBS 10 LBS	4/15-6/15	4/15-6/30	4/15-6/30
MILLET, PEARL	1.1 LBS	50 LBS	5/15-7/15	5/1-7/31	4/15-8/15
OATS ALONE OATS IN MIXTURES	2.99 LBS 0.7 LBS	4.0 BU 1.0 BU	9/15-11/15	9/15-11/15	9/15-11/15
RYE (GRAIN) ALONE RYE IN MIXTURES	3.9 LBS 0.6 LBS	3.0 BU 0.5 BU	8/15-10/31	9/15-11/30	10/1-12/31
RYEGRASS	0.9 LBS	40 LBS	8/15-11/15	9/1-12/15	9/15-12/31
SUDANGRASS	1.4 LBS	60 LBS	5/31-7/31	5/31-7/31	4/1-7/31
TRITICALE ALONE TRITICALE IN MIXTURES	3.3 LBS 0.6 LBS	3.0 BU 0.5 BU	N/A	N/A	10/15-11/30
WHEAT ALONE WHEAT IN MIXTURES	4.1 LBS 0.7 LBS	3.0 BU 0.5 BU	9/15-11/30	10/1-12/15	10/15-12/31

TABLE 2: FERTILIZER REQUIREMENTS FOR TEMPORARY VEGETATION

TYPES OF SPECIES	PLANTING YEAR	FERTILIZER (N-P-K)	RATE (LBS/ACRE)	N TOP DRESSING RATE (LBS/ACRE)
COOL SEASON GRASSES	FIRST SECOND MAINTENANCE	6-12-12 6-12-12 10-10-10	1500 1000 400	50-100 30
COOL SEASON GRASSES & LEGUMES	FIRST SECOND MAINTENANCE	6-12-12 0-10-10 0-10-10	1500 1000 400	0-50
TEMPORARY COVER CROPS SEEDED ALONE	FIRST	10-10-10	500	30
WARM SEASON GRASSES	FIRST SECOND MAINTENANCE	6-12-12 6-12-12 10-10-10	1500 800 400	50-100 50-100 30

GSWCC GEORGIA SOIL AND WATER CONSERVATION COMMISS Alec B Metzger

CERTIFICATION NUMBER: 0000008757

LEVEL II CERTIFIED DESIGN PROFESSIONAL





PROJECT NO.: DRAWN BY: MRK DESIGNED BY: MRK SURVEYED BY: BREWER SURVEY DATE: 2018 CHECKED BY: ABM SCALE: DATE: JANUARY 2025


SHEET


TYPICAL INSTALLATION GUIDELINES FOR ROLLED EROSION CONTROL PRODUCTS (RECP) Ss



























NO.	REVISION DESCRIPTION	DATE
~	REVISIONS PER CITY OF POOLER	9/1/2021
2	REVISIONS PER CITY OF POOLER	10/26/202
3	REVISIONS PER CITY OF POOLER	11/ /2021
4	REVISIONS PER CITY OF POOLER	8/1/2023
-\$-	OWNER REVISIONS	1/24/25
1	-	•






PROJECT NO.: DRAWN BY: MRK DESIGNED BY: MRK SURVEYED BY: BREWER SURVEY DATE: CHECKED BY: ABM SCALE: N/A JANUARY 2025


DATE: SHEET


"SANITARY SEWER"
TO BE CAST ON COVER


CITY OF POOLER


2011 STANDARD DETAIL













MANHOLE COVER & FRAME DETAIL





1: CASTINGS SHALL BE OF UNIFORM QUALITY, FREE FROM BLOWHOLES, POROSITY, HARD SPOTS, SHRINKAGE, DISTORTION OR OTHER DEFECTS THEY SHALL BE SMOOTH AND WELL CLEANED BY SHOTBLASTING OR BY SOME OTHER APPROVED METHOD. CASTING SHALL NOT BE PAINTED.


: MATERIALS USED IN THE MANUFACTURE OF CASTINGS SHOULD CONFORM AASHO M105/ASTM A48, CLASS 358 OF ASTM A48, CLASS 3D, FOR GRAY


RISER RING FOR UPWARD ADJUSTMENT OF COVER. CLEAR OPENING SHALL BE 24". 4: MANHOLE COVER SHALL BE $25-3/4^{\prime\prime}$ IN DIAMETER AND SHALL BE 2-INCHES THICK AT THE BEARING SURFACE.


August 2006


 CASTINGS SHALL BE PROVIDED WITH THE INSCRIPTION "SANITARY SEWER"
CAST INTO THE COVER IN LETTERING AT LEAST 2-INCHES HIGH.
MANUFACTURER'S NAME, IF IT APPEARS ON THE COVER, SHALL
BE CONFINED TO THE PERIPHERY. 6. MANHOLE COVERS AND FRAMES SHALL BE USF 227, TYPE "AS" OR EQUAL. 7. USE WATER TIGHT MANHOLE RINGS AND COVERS WITHIN OR BELOW BASE FLOOD ELEVATION +1 FT (STANDARD SPECIFICATIONS 02720.202.G.2)

3: ALL CASTINGS SHALL BE MANUFACTURED TRUE TO PATTERN:
COMPONENT PARTS SHALL FIT TOGETHER IN A SATISFACTORY MANNER,
ROUND FRAMES AND COVERS SHALL BE OF NON-ROCKING DESIGN, OR SHA
HAVE MACHINED BEARING SURFACES TO PREVENT ROCKING AND RATITLING
UNDER TRAFFIC. FRAME SHALL BE SUITABLE FOR CAST IRON OR STEEL









SURVEY DATE:

CHECKED BY:

SHEET

SCALE:


DATE:


2018


ABM


N/A


JANUARY 2025























PERMEABLE PAVER DETAIL

NOT TO SCALE

	NO.	NO. REVISION DESCRIPTION
	1	REVISIONS PER CITY OF POOLER
/v.	2	REVISIONS PER CITY OF POOLER
0	3	REVISIONS PER CITY OF POOLER
R G	4	REVISIONS PER CITY OF POOLER
	-5-	OWNER REVISIONS
//	-	-




OMMERCIAL


PROJECT NO.: 20-0130 DRAWN BY: MRK DESIGNED BY: MRK SURVEYED BY: BREWER SURVEY DATE: 2018 CHECKED BY: ABM SCALE: N/A


JANUARY 2025

SHEET

DATE:









CONSTRUCTION DETAILS

COMMERCIAL SPACE
780 POOLER PARKWAY
POOLER, CHATHAM COUNTY, GEORGIA
Prepared for:
COMBAT VETERANS, LLC

PROJECT NO.:
DRAWN BY:
DESIGNED BY:
SURVEYED BY:
SURVEY DATE:
CHECKED BY:
SCALE:
DATE: 20-0130 MRK MRK BREWER

2018
ABM
N/A
JANUARY 2025

SHEET 18